

Bryant Development and Review Committee Meeting

Boswell Municipal Complex - City Hall Conference Room 210 SW 3rd Street

Date: September 28, 2023 - Time: 9:00 AM

Call to Order

Old Business

New Business

1. Hilldale Crossing Ph.3 - Final Plat

Hope Consulting- Requesting Recommendation for Final Plat Approval

- · 0689-ASB-01.pdf
- 0689-ASB-02.pdf
- <u>0792-APP-01.pdf</u>
- 0792-BNDLTR-01.pdf
- <u>0792-LTR-01.pdf</u>
- 0792-PLT-01.pdf

2. REQUEST TO ADD: Summerwoods Sports Complex - Gym 3 - Bryant Parkway and Hwy 5

PLE Engineering - Requesting Recommendation for Site Plan Approval

- <u>0783-RPLT-01.pdf</u>
- · 0783-DRN-01.pdf
- 0783-PLN-02.pdf

Staff Approved

3. Springhill Grocery - Delek Oil - 2725 Springhill Road


Edwards Sign Company - Requesting Sign Permit Approval - STAFF APPROVED


- · 0789-APP-01.pdf
- 0787-APP-01.pdf

Permit Report

Adjournments









SANITARY SEWER AND WATER AS-BUILTS HILLDALE CROSSING PHASE 2

A SUBDIVISION IN SALINE COUNTY, ARKANSAS











FOR USE AND BENEFIT OF: HAVENS DEVELOPMENT, LLC


WATER & SEWER AS-BUILTS PLAN
HILLDALE CROSSING PHASE 2
A SUBDIVISION IN SALINE COUNTY, ARKANSAS

ı										
	DATE:	12/20/2021		C.A.D. BY: B.JOHNSON				DRAWING NUMBER:		
	REVISED:		CHEC	CKEI	O BY:		20-0169			
	KEVISED:		SCAL	SCALE: 1"=50'						
	500	018	1/	1 \ \\	\cap	03	330		62	1762









DRAINAGE AS-BUILTS HILLDALE CROSSING PHASE 2

A SUBDIVISION IN SALINE COUNTY, ARKANSAS





FOR USE AND BENEFIT OF: HAVENS DEVELOPMENT, LLC

DRAINAGE AS-BUILTS PLAN HILLDALE CROSSING PHASE 2 A SUBDIVISION IN SALINE COUNTY, ARKANSAS

DATE:	12/20/2022		C.A.D. BY: B.JOHNSON				DRAWING NUMBER:		
REVISED:			CHECKED BY:			20-0169			
KEVISED:			SCALE: 1"=50'						
500	018	1,	1 \ \\	Ω	03	330		62	1762



Subdivision Checklist

Approved by Bryant Planning Commission 07/14/2003 Revised 6/18/2007

Instructions

The attached checklist must be completed by the owner and subdivision engineer and must be submitted along with the Preliminary Plat Plan and other specified documentation for review and approval by the Planning Commission. The owner may not begin developing the subdivision until the review of the Preliminary Plat plan is approved.

No changes or alterations can be made to the approved Preliminary Plat Plan without Planning Commission approval.

When all lots have been surveyed, the utilities and drainage measures are in place, and roads have been constructed, the owner and engineer will submit a Final Plat Plan for approval by the Commission. This Final Plat Plan will incorporate all approved changes and will be verified by the City Engineer. No lots will be sold or rights-of-way and easements conveyed until the Final Plat has been submitted and approved.

Fees due to City of Bryant upon submission of Preliminary Plat application

- \$300.00 + \$3.00 per lot for Subdivision preliminary plat review
- \$250.00 or \$25.00 per lot (whichever is greater) Stormwater Detention and Drainage Plan Engineering Fee
- A Surety Bond or Cashier's check in the amount of 10% of the estimated development cost must be furnished within 10 days after Preliminary Plat approval.

Fees due to Bryant Water and Sewer Department upon submission of Final Plat application

- \$100 per lot Water/Sewer Impact Fee
- \$100 per Subdivision Phase Water/Sewer Flushing Fee

Fees due to City of Bryant upon submission of Final Plat application

\$25.00 + \$1.00 per lot - for Subdivision Final Plat review

Final Plat Fees

Check Payable to City of Bryant for Review fee of \$63 Check Payable to Bryant Water and Sewer Department for \$7,600

City of Bryant Subdivision Checklist

Sub	divisi	on/Project NameHilldale Crossing											
Con	tact i	PersonJonathan Hope	Phone	501-860-0467									
AA ~ 41	ina A	129 N. Main Street Benton, Arkansas											
maii	Mailing Address												
	I. B. and harmon various Name of Co. Tora David												
i. c	PASIC	INFORMATION NEEDED ON THE PLAT											
١.	1.	Name of Subdivision/Project											
	2.	Current zoning N/A											
`,	3.	Name and Address of owner of Record											
	4.	Illustrate Source of Title giving deed record book and page	number										
1	5.	Name & address of the sub-divider											
	6.	Date of Survey											
	7.	Vicinity map locating streets, highways, section lines, railro	ad, schoo	ls, & parks within ½ mile									
1	8.	Legal description of the property with exact boundary lines											
1	9.			,									
1		Number of Lots											
1		Lot area in square feet											
1		Lot lines with appropriate dimensions											
1		Building setback lines	-h										
1		Preliminary Engineering certificate seal and signature on ea	cn page										
1		Certificate of Engineering Accuracy											
1		Certificate of Final Plat Approval											
1		Certificate of Final Plat Approval											
1		Certificate of Recording Show scale (not less than 1" = 100')											
1		North Arrow											
1		Show Title block											
1		Show adjoining property owners											
1		Layout of all proposed streets including traffic control device	es (stop s	igns, speed limit, etc.)									
/		Layout of all subdivision entrance street upgrades	(0.10)	.g., .p									
_		Layout of all proposed alleys											
1		Layout of all proposed sidewalk systems											
	27.	Layout identifies any FEMA flood plain and flood way proper	ty within	the 100-year flood elevation.									
		(Provide Corp of Engineers 404 Permit if required)											
		Drainage easements for stormwater run-off and detention gi											
		Layout accommodates Master Street Plan segments within the											
_	30.	Street layout ties to existing adjoining subdivision stub-out s	streets and	d provides stub-out streets for									
	24	future adjoining subdivisions.	ional dae	rification									
		Street width and right-of-way properly shown for each funct Street centerlines showing angles of deflection, intersection											
	JZ.	degree of curvature with basis of curve data	i, rauli, (C	ngan orangenas and arcs, and									
	33.	Typical cross section of streets											
V		Location and name of existing streets											
V		New street names that are not similar to existing street nam	nes										
V		Show street lights											

▲ 37. Show Fire Hydrant placement

- ▲ 38. Show and label all permanent & proposed easements
- ▲ 39. Any proposed open space must be shown
 - ▲ 40. Show the direction and flow of all water courses entering the tract
- ▲ 41. Show the direction and flow of all water courses leaving the tract
 - ▲ 42. The drainage area of all water courses above the points of entry.
 - ▲ 43. The downstream drainage channel and drainage structures substantially impacted by the subdivision/project.
- ▲ 44. Show source of water supply

 $\sqrt{}$

- ▲ 45. Show location of waste water connection to municipal main & sanitary sewer layout
- ▲ 46. A phasing plan outlining the boundaries for each phase

II. ADDITIONAL INFORMATION NEEDED, BUT NOT NECESSARILY ON THE PLAT

- ▲ 47. Natural features within the proposed subdivision including drainage channels, bodies of water, wooded areas, and other significant features
- ▲ 48. Existing streets, buildings, water courses, railroads. Culverts, utilities and easement on and adjacent to the tract.
- ▲ 49. Where method of disposal of wastewater is other than connection to a public waste water system, detailed information shall accompany the plat.
- ▲ 50. Calculations and field notes, including drainage calculations along with support drawing
 - 51. Stormwater detention plan approval from City Engineer (attach copy of approval)
- ▲ 52. The Certificate of Preliminary Engineering Accuracy on each set of street and drainage plans.
 - ▲ 53. ADA Accessibility Standard Form completed (and attached)
 - ▲ 54. A Bill of Assurance has been prepared for this subdivision (and attached)
 - ▲ 55. All lots comply with minimum square footage area and minimum lot width at the front building line
 - ▲ 56. Street pavement design will be as specified by City or AHTD design procedures, approved by the City Engineer.
 - ▲ 57. Made the "One Call" prior to site clearance or other excavation activity

III. PRELIMINARY PLAT ATTACHMENTS

(APPLICATION WILL NOT BE ACCEPTED UNTIL ALL ATTACHMENT REQUIREMENTS ARE MET)

- ▲ 58. Letter to Planning Commission stating your request
- ▲ 59. Completed Checklist

 $\sqrt{}$

 $\sqrt{}$

- ▲ 60. Completed agreement to provide performance assurance
- ▲ 61. Subdivider Performance Bond or Cashier's Check for infrastructure installation
- ▲ 62. Landscaping plan of any proposed common open space
- ▲ 63. **Draft of Bill of Assurance** proposed for the subdivision (if applicable)
- ▲ 64. **20 copies of Preliminary Plat Plan (folded)** that includes vicinity map (minimum size 17" X 34" paper)
- ▲ 65. <u>Two</u> (2) IBM compatible diskettes or CDR's with pertinent data and Plat in CAD compatible .DXF electronic file format
- ▲ 66. Copy of Stormwater Detention approval
- ▲ 67. 2 copies Plan and profile of all streets
- ▲ 68. Receipt for \$300.00 + \$3.00 per lot for preliminary Subdivision fee
- ▲ 69. Receipt for \$250.00 or \$25.00 per lot (whichever is greater) for Stormwater Detention and Drainage Plan review
- ▲ 70. Copy of ADEQ Stormwater Pollution Prevention Plan for property parcel containing one acre or larger.

III. FINAL PLAT ATTACHMENTS

(APPLICATION WILL NOT BE ACCEPTED UNTIL ALL ATTACHMENT REQUIREMENTS ARE MET)

- ▲ 71. Letter to Planning Commission stating your request
- ▲ 72. Completed Checklist
- → 73. 20 copies of Final Plat Plan (folded) that includes vicinity map (minimum size 17" X 34" paper)
- ▲ 74. Two (2) IBM compatible diskettes or CDR's with pertinent data and Plat in CAD compatible .DXF electronic file format
- ▲ 75. Bill of Assurance including provisions set out in Title 15 Subdivision Regulations 15.16.01
- ▲ 76. Copy of Water & Sewer Commission approval or....
- ▲ 77. State Health Department approval of any new water supply and/or sewage system.
- ▲ 78. Letter submitted by a Registered Professional Engineer, certifying that all infrastructure improvements and installations have been installed in accordance with the submitted construction plans and drawings and the standards established by the City of Bryant and are functioning properly.
- ▲ 79. Infrastructure Maintenance Bond or Cashier's check.
- ▲ 80. Check for \$25.00 + \$1.00 per lot for final Subdivision fee
- ▲ 81. Check for Water Sewer impact fees (\$100.00 Flushing Fee and \$100.00 impact fee per lot)

Hilldale Crossing	Jonathan Hope							
Name of Subdivision	Surveyor							
I HAVE COMPLIED WITH THE REQUIREM CHECKLIST WHICH APPLY TO THIS PRO	MENTS LISTED ABOVE AND HAVE CHECKED ALL OF THE BOXES ON THE DJECT SUBMITTAL.							
Owner Signature	Engineer Signature							
CITY USE								
Preliminary Plat Approved								
Planning Commission Date								
Final Plat Approved								
Planning Commission Date								
Proof of Recording - County								
County Clerk	Date							



Saline County Road Department 5500 Cynamide Road Benton, Arkansas 72015 (501) 303-5690

September 26, 2023

Havens Development 2615 North Prickett, Suite 5 Bryant, AR 72022

Ref: Maintenance Bond to Cover Roads in Hilldale Crossing Phase 3

Dear Mr. Havens;

The maintenance bond to ensure that Havens Development will either correct any defects that arise or that Saline County is compensated for costs resulting from repairs of any defects identified for a period of one year is required. The amount of bond is calculated as \$25.00 per constructed foot of street. Based on the Final Plat, the footage of constructed roads is 1276 feet.

Required Maintenance Bond is 1276' x \$25.00 = \$31,900.0.

The date of expiration of this bond will be one year after the date of bond creation.

Thanks,
John Wofford PE, PLS

Saline County Engineer.



September 26, 2023

Truett Smith City of Bryant 210 Southwest Third St., Bryant, AR 72022

RE: Hilldale Final Plat Phase 3

Dear Truett:

On behalf of the property owner, Hope Consulting is requesting the final review of this residential subdivision project located in the Bryant ETJ. This subdivision development consists of sewer provided by Bryant, Water provided by Water Users, and Electric provided by First Electric. We are submitting to start the review for the Final plat. It is the desire of our client to be on the October Planning Commission agenda.


The developer of this project is Todd and Callie Havens of Havens Development.


Todd Havens: todd@havensdev.com

Please feel free to contact me with any questions or concerns or if I can be of any further assistance.

Sincerely,

Jonathan Hope





REVISIONS DATE

A REPLAT ADDITION


SERVIC ROBBINS PROFESSION

/ DRAWN BY DESIGNED CHECKED DATE 9-20-23 SCALE 1" = 30' PROJECT NO. 2023225

SUMMERWOOD SPORTS GYM #3 DRAINAGE REPORT

LOCATED IN BRYANT, ARKANSAS

Prepared by:



PHILLIP LEWIS ENGINEERING

Structural + Civil Consultants

23620 Interstate 30 | Bryant, AR PH: 501-350-9840



PROJECT LOCATION MAP



Vacinity Map

PROJECT SUMMARY

The proposed project is for the consruction of the third gymnasium of the Summerwood Sports Complex located along Bryant Parkway and Hwy 5.

The proposed development is for a 30,000 sq. ft. building and parking lot that will utilize curb/gutter and concrete/asphalt to direct stormwater to the designated catch basins. The existing detention basin that was constructed for the first two gymnasiums will be abanoned to construct the new proposed gymnasium. A regional detention basin will be installed in the northwest corner of the remaining parcel to serve the entirety of the complex property.


The existing storm sewer network will be interupted with new storm sewer and routed to the new detention basin. This regional detention basin is designed to allow the future to be developed at a rate of 80% impervious.

A stormwater analysis was ran on the development using HydroCAD software. Stormwater calculations were setup and run for the 2, 5, 10, 25, 50, and 100-year storm event using the rational method.

The final release rate of the detention pond is controlled by a 6" orificace cast into a concrete outlet structure, including an open top that allows flow to increase past the 2' ponding depth in the pond. Ponding past the 2' depth is then controlled by a single 24" rcp releasing at the east adjacent property line.

Post-development runoff rates were held to below pre-development runoff rates.

The results of the analysis for both pre-development and post-development, including the change in runoff volume and runoff rate, are shown below within the attached report.



Prepared by Phillip Lewis Engineering

HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Subcatchment DB-A1: Drainage Basin A1


Runoff = 6.18 cfs @ 0.09 hrs, Volume= 5,559 cf, Depth= 0.65"

Routed to Link Pre: Pre Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 2-yr Duration=15 min, Inten=3.54 in/hr

	Α	rea (sf)	С	Description)	
	1	01,860	0.74			
_	1	01,860		100.00% P	ervious Are	ea
	Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
_	5.0	415		1 38		Direct Entry, Overland Concentrated Flow (Min)

Subcatchment DB-A1: Drainage Basin A1



Prepared by Phillip Lewis Engineering

HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Subcatchment DB-A2: Drainage Basin A2


Runoff = 10.17 cfs @ 0.09 hrs, Volume= 9,157 cf, Depth= 0.65"

Routed to Link Pre: Pre Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 2-yr Duration=15 min, Inten=3.54 in/hr

_	Α	rea (sf)	С	Description	1	
	1	67,793	0.74			
	167,793 100.00% Pervious Area					ea
	Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
	5.0	402		1.34		Direct Entry, Overland Concentrated Flow (Min)

Subcatchment DB-A2: Drainage Basin A2



Summary for Subcatchment DB-A3: Drainage Basin A3


Runoff = 16.84 cfs @ 0.25 hrs, Volume= 15,154 cf, Depth= 0.51"

Routed to Link Pre: Pre Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 2-yr Duration=15 min, Inten=3.54 in/hr

	Ar	ea (sf)	С	Description	1	
	3	59,120	0.74			_
	3	59,120		100.00% P	ervious Are	ea ea
(m	Tc nin)	Length (feet)	Slope (ft/ft)		Capacity (cfs)	Description
1	3.7	300	0.0420	0.37		Sheet Flow, Overland Sheet Flow
	1.2	103	0.0430	1.45		Range n= 0.130 P2= 4.19" Shallow Concentrated Flow, Overland Concentrated Flow Short Grass Pasture Kv= 7.0 fps
	1.7	150	0.0460	1.50		Shallow Concentrated Flow, Overland Concentrated Flow
	2.8	225	0.0360	1.33		Short Grass Pasture Kv= 7.0 fps Shallow Concentrated Flow, Overland Concentrated Flow Short Grass Pasture Kv= 7.0 fps
1	9.4	778	Total			

Subcatchment DB-A3: Drainage Basin A3



Summary for Subcatchment DB-A4: Drainage Basin A4


Runoff = 2.43 cfs @ 0.19 hrs, Volume= 2,183 cf, Depth= 0.65"

Routed to Link Pre: Pre Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 2-yr Duration=15 min, Inten=3.54 in/hr

	A	rea (sf)	С	Description	1	
•		40,000	0.74	•		
40,000 100.00% Pervi						ea
	Tc (min)	Length (feet)	Slope (ft/ft)	•	Capacity (cfs)	Description
•	3.8	50	0.0390	0.22	,	Sheet Flow, Overland Sheet Flow
	6.4	114	0.0530	0.30		Grass: Short n= 0.150 P2= 4.19" Sheet Flow, Overland Sheet Flow Crass: Short n= 0.150 P2= 4.40"
	0.9	91	0.0600	1.71		Grass: Short n= 0.150 P2= 4.19" Shallow Concentrated Flow, Overland Concentrated Flow Short Grass Pasture Kv= 7.0 fps
•	11 1	255	Total			<u> </u>

Subcatchment DB-A4: Drainage Basin A4



Summary for Subcatchment DB-A5: Drainage Basin A5


Runoff = 1.93 cfs @ 0.09 hrs, Volume= 1,733 cf, Depth= 0.65"

Routed to Link Pre: Pre Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 2-yr Duration=15 min, Inten=3.54 in/hr

	Α	rea (sf)	С	Description)		
		31,762	0.74				
		31,762		100.00% P	ervious Are	ea	
	Tc (min)	Length (feet)	Slope (ft/ft)	•	Capacity (cfs)	Description	
_	5.2	111	0.0850	0.35	, ,	Sheet Flow, Overland Sheet Flow	_
	0.2	23	0.0680	1.91		Grass: Short n= 0.150 P2= 4.19" Sheet Flow, Overland Sheet Flow Smooth surfaces n= 0.011 P2= 4.19"	
	5 4	134	Total				

Subcatchment DB-A5: Drainage Basin A5



Summary for Subcatchment DB-A6: Drainage Basin A6


Runoff = 6.30 cfs @ 0.25 hrs, Volume= 5,674 cf, Depth= 0.52"

Routed to Link Pre: Pre Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 2-yr Duration=15 min, Inten=3.54 in/hr

	Aı	rea (sf)	С	Description	١	
	1	30,999	0.74			
130,999				100.00% P	ervious Are	ea
	Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
-	16.9	300	0.0330	0.30	, ,	Sheet Flow, Overland Sheet Flow
	2.0	150	0.0330	1.27		Grass: Short n= 0.150 P2= 4.19" Shallow Concentrated Flow, Overland Concentrated Flow Short Grass Pasture Kv= 7.0 fps
	18.9	450	Total			

Subcatchment DB-A6: Drainage Basin A6



Summerwood Gym 3

AR - Little Rock 2-yr Duration=15 min, Inten=3.54 in/hr
Printed 9/19/2023

Prepared by Phillip Lewis Engineering
HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Link Pre: Pre Development


Inflow Area = 831,534 sf, 0.00% Impervious, Inflow Depth = 0.57" for 2-yr event

Inflow = 44.01 cfs @ 0.25 hrs, Volume= 39,461 cf

Primary = 44.01 cfs @ 0.25 hrs, Volume= 39,461 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs

Link Pre: Pre Development



Prepared by Phillip Lewis Engineering

HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Subcatchment DB-A1: Drainage Basin A1


Runoff = 7.33 cfs @ 0.09 hrs, Volume= 6,595 cf, Depth= 0.78"

Routed to Link Pre: Pre Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 5-yr Duration=15 min, Inten=4.20 in/hr

_	Α	rea (sf)	С	Description	1	
	1	01,860	0.74			
	1	01,860		100.00% P	ervious Are	ea
	Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
_	5.0	415	(12,12)	1.38	(0.0)	Direct Entry, Overland Concentrated Flow (Min)

Subcatchment DB-A1: Drainage Basin A1



Prepared by Phillip Lewis Engineering

HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Subcatchment DB-A2: Drainage Basin A2


Runoff = 12.07 cfs @ 0.09 hrs, Volume= 10,865 cf, Depth= 0.78"

Routed to Link Pre: Pre Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 5-yr Duration=15 min, Inten=4.20 in/hr

_	Α	rea (sf)	С	Description	1	
	1	67,793	0.74			
	167,793 100.00% Pervious Area					ea
	Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
	5.0	402		1.34		Direct Entry, Overland Concentrated Flow (Min)

Subcatchment DB-A2: Drainage Basin A2



Summerwood Gym 3

Prepared by Phillip Lewis Engineering

HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Subcatchment DB-A3: Drainage Basin A3


Runoff = 19.98 cfs @ 0.25 hrs, Volume= 17,979 cf, Depth= 0.60"

Routed to Link Pre: Pre Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 5-yr Duration=15 min, Inten=4.20 in/hr

	Α	rea (sf)	С	Description)	
_	3	59,120	0.74			
	3	59,120		100.00% P	ervious Are	ea
	Tc (min)	Length (feet)	Slope (ft/ft)	,	Capacity (cfs)	Description
	13.7	300	0.0420	0.37		Sheet Flow, Overland Sheet Flow
	1.2	103	0.0430	1.45		Range n= 0.130 P2= 4.19" Shallow Concentrated Flow, Overland Concentrated Flow Short Grass Pasture Kv= 7.0 fps
	1.7	150	0.0460	1.50		Shallow Concentrated Flow, Overland Concentrated Flow
	2.8	225	0.0360	1.33		Short Grass Pasture Kv= 7.0 fps Shallow Concentrated Flow, Overland Concentrated Flow Short Grass Pasture Kv= 7.0 fps
	19.4	778	Total			

Subcatchment DB-A3: Drainage Basin A3



Summerwood Gym 3

Prepared by Phillip Lewis Engineering

HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Subcatchment DB-A4: Drainage Basin A4


Runoff = 2.88 cfs @ 0.19 hrs, Volume= 2,590 cf, Depth= 0.78"

Routed to Link Pre: Pre Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 5-yr Duration=15 min, Inten=4.20 in/hr

Α	rea (sf)	С	Description	1	
	40,000	0.74			
	40,000		100.00% P	ervious Are	ea
Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
3.8	50	0.0390	0.22		Sheet Flow, Overland Sheet Flow
6.4	114	0.0530	0.30		Grass: Short n= 0.150 P2= 4.19" Sheet Flow, Overland Sheet Flow
0.9	91	0.0600	1.71		Grass: Short n= 0.150 P2= 4.19" Shallow Concentrated Flow, Overland Concentrated Flow Short Grass Pasture Kv= 7.0 fps
11.1	255	Total			·

Subcatchment DB-A4: Drainage Basin A4



Summary for Subcatchment DB-A5: Drainage Basin A5


Runoff = 2.29 cfs @ 0.09 hrs, Volume= 2,057 cf, Depth= 0.78"

Routed to Link Pre: Pre Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 5-yr Duration=15 min, Inten=4.20 in/hr

	Α	rea (sf)	С	Description)	
		31,762	0.74			
		31,762		100.00% P	ervious Are	ea
	Tc (min)	Length (feet)	Slope (ft/ft)	,	Capacity (cfs)	Description
-	5.2	111	0.0850	0.35		Sheet Flow, Overland Sheet Flow
	0.2	23	0.0680	1.91		Grass: Short n= 0.150 P2= 4.19" Sheet Flow, Overland Sheet Flow Smooth surfaces n= 0.011 P2= 4.19"
	5.4	134	Total	•		

Subcatchment DB-A5: Drainage Basin A5



Summary for Subcatchment DB-A6: Drainage Basin A6


Runoff = 7.48 cfs @ 0.25 hrs, Volume= 6,732 cf, Depth= 0.62"

Routed to Link Pre: Pre Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 5-yr Duration=15 min, Inten=4.20 in/hr

	Aı	rea (sf)	С	Description	١	
	1	30,999	0.74			
130,999				100.00% P	ervious Are	ea
	Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
-	16.9	300	0.0330	0.30	, ,	Sheet Flow, Overland Sheet Flow
	2.0	150	0.0330	1.27		Grass: Short n= 0.150 P2= 4.19" Shallow Concentrated Flow, Overland Concentrated Flow Short Grass Pasture Kv= 7.0 fps
	18.9	450	Total			

Subcatchment DB-A6: Drainage Basin A6



Prepared by Phillip Lewis Engineering

HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Link Pre: Pre Development


Inflow Area = 831,534 sf, 0.00% Impervious, Inflow Depth = 0.68" for 5-yr event

Inflow = 52.21 cfs @ 0.25 hrs, Volume= 46,818 cf

Primary = 52.21 cfs @ 0.25 hrs, Volume= 46,818 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs

Link Pre: Pre Development



Prepared by Phillip Lewis Engineering

HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Subcatchment DB-A1: Drainage Basin A1


Runoff = 8.31 cfs @ 0.09 hrs, Volume= 7,475 cf, Depth= 0.88"

Routed to Link Pre: Pre Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 10-yr Duration=15 min, Inten=4.76 in/hr

_	Α	rea (sf)	С	Description	1	
	1	01,860	0.74			
	101,860 100.00% Pervious Area				ervious Are	ea
_	Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
_	5.0	415		1.38		Direct Entry, Overland Concentrated Flow (Min)

Subcatchment DB-A1: Drainage Basin A1



Summary for Subcatchment DB-A2: Drainage Basin A2


Runoff = 13.68 cfs @ 0.09 hrs, Volume= 12,313 cf, Depth= 0.88"

Routed to Link Pre: Pre Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 10-yr Duration=15 min, Inten=4.76 in/hr

_	Α	rea (sf)	С	Description	ı	
	1	67,793	0.74			
	167,793 100.00% Pervious Area				ervious Are	ea
_	Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
	5.0	402	•	1.34		Direct Entry, Overland Concentrated Flow (Min)

Subcatchment DB-A2: Drainage Basin A2



Summerwood Gym 3

Prepared by Phillip Lewis Engineering

HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Subcatchment DB-A3: Drainage Basin A3


Runoff = 22.64 cfs @ 0.25 hrs, Volume= 20,376 cf, Depth= 0.68"

Routed to Link Pre: Pre Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 10-yr Duration=15 min, Inten=4.76 in/hr

_	Α	rea (sf)	С	Description]	
	3	59,120	0.74			
	359,120 100.00% Per				ervious Are	ea
	Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
_	13.7	300	0.0420	0.37	, ,	Sheet Flow, Overland Sheet Flow
	4.0	400	0.0400	4 45		Range n= 0.130 P2= 4.19"
	1.2	103	0.0430	1.45		Shallow Concentrated Flow, Overland Concentrated Flow Short Grass Pasture Kv= 7.0 fps
	1.7	150	0.0460	1.50		Shallow Concentrated Flow, Overland Concentrated Flow
						Short Grass Pasture Kv= 7.0 fps
	2.8	225	0.0360	1.33		Shallow Concentrated Flow, Overland Concentrated Flow
_						Short Grass Pasture Kv= 7.0 fps
	19.4	778	Total			

Subcatchment DB-A3: Drainage Basin A3



Summary for Subcatchment DB-A4: Drainage Basin A4


Runoff = 3.26 cfs @ 0.19 hrs, Volume= 2,935 cf, Depth= 0.88"

Routed to Link Pre: Pre Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 10-yr Duration=15 min, Inten=4.76 in/hr

	A	rea (sf)	С	Description	1	
•		40,000	0.74	•		
•		40,000		100.00% P	ervious Are	ea
	Tc (min)	Length (feet)	Slope (ft/ft)	•	Capacity (cfs)	Description
•	3.8	50	0.0390	0.22	,	Sheet Flow, Overland Sheet Flow
	6.4	114	0.0530	0.30		Grass: Short n= 0.150 P2= 4.19" Sheet Flow, Overland Sheet Flow Crass: Short n= 0.150 P2= 4.40"
	0.9	91	0.0600	1.71		Grass: Short n= 0.150 P2= 4.19" Shallow Concentrated Flow, Overland Concentrated Flow Short Grass Pasture Kv= 7.0 fps
•	11 1	255	Total			<u> </u>

Subcatchment DB-A4: Drainage Basin A4



Summary for Subcatchment DB-A5: Drainage Basin A5


Runoff = 2.59 cfs @ 0.09 hrs, Volume= 2,331 cf, Depth= 0.88"

Routed to Link Pre: Pre Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 10-yr Duration=15 min, Inten=4.76 in/hr

	Α	rea (sf)	С	Description	1		
		31,762	0.74				
31,762 100.00% Pervious Area						ea	
	Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description	
•	5.2	111	0.0850	0.35	, ,	Sheet Flow, Overland Sheet Flow	
	0.2	23	0.0680	1.91		Grass: Short n= 0.150 P2= 4.19" Sheet Flow, Overland Sheet Flow Smooth surfaces n= 0.011 P2= 4.19"	
•	5.4	13/	Total	•	•		

Subcatchment DB-A5: Drainage Basin A5



Summary for Subcatchment DB-A6: Drainage Basin A6


Runoff = 8.48 cfs @ 0.25 hrs, Volume= 7,629 cf, Depth= 0.70"

Routed to Link Pre: Pre Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 10-yr Duration=15 min, Inten=4.76 in/hr

_	A	rea (sf)	С	Description	1	
_	1	30,999	0.74			
_	1	30,999		100.00% P	ervious Are	ea
	Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
_	16.9	300	0.0330	0.30	(212)	Sheet Flow, Overland Sheet Flow
	2.0	150	0.0330	1.27		Grass: Short n= 0.150 P2= 4.19" Shallow Concentrated Flow, Overland Concentrated Flow Short Grass Pasture Kv= 7.0 fps
_	18.9	450	Total			

Subcatchment DB-A6: Drainage Basin A6



Summerwood Gym 3

AR - Little Rock 10-yr Duration=15 min, Inten=4.76 in/hr Printed 9/19/2023

Prepared by Phillip Lewis Engineering
HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Link Pre: Pre Development


Inflow Area = 831,534 sf, 0.00% Impervious, Inflow Depth = 0.77" for 10-yr event

Inflow = 59.17 cfs @ 0.25 hrs, Volume= 53,060 cf

Primary = 59.17 cfs @ 0.25 hrs, Volume= 53,060 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs

Link Pre: Pre Development



Summary for Subcatchment DB-A1: Drainage Basin A1


Runoff = 9.49 cfs @ 0.09 hrs, Volume= 8,543 cf, Depth= 1.01"

Routed to Link Pre: Pre Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 25-yr Duration=15 min, Inten=5.44 in/hr

_	Α	rea (sf)	С	Description	1	
	1	01,860	0.74			
	101,860 100.00% Pervious Area					ea
	Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
_	5.0	415	(13,11)	1.38	(0.0)	Direct Entry, Overland Concentrated Flow (Min)

Subcatchment DB-A1: Drainage Basin A1



HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Subcatchment DB-A2: Drainage Basin A2


Runoff = 15.64 cfs @ 0.09 hrs, Volume= 14,072 cf, Depth= 1.01"

Routed to Link Pre: Pre Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 25-yr Duration=15 min, Inten=5.44 in/hr

_	Α	rea (sf)	С	Description)	
	1	67,793	0.74			
_	167,793 100.00% Pervious Area					ea
_	Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
	5.0	402		1.34		Direct Entry, Overland Concentrated Flow (Min)

Subcatchment DB-A2: Drainage Basin A2



Prepared by Phillip Lewis Engineering

HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Subcatchment DB-A3: Drainage Basin A3


Runoff = 25.87 cfs @ 0.25 hrs, Volume= 23,287 cf, Depth= 0.78"

Routed to Link Pre: Pre Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 25-yr Duration=15 min, Inten=5.44 in/hr

	Α	rea (sf)	С	Description	1	
	3	59,120	0.74			
_	359,120 100.00% Pervious A				ervious Are	ea
_	Tc (min)	Length (feet)	Slope (ft/ft)	,	Capacity (cfs)	Description
	13.7	300	0.0420	0.37		Sheet Flow, Overland Sheet Flow
	1.2	103	0.0430	1.45		Range n= 0.130 P2= 4.19" Shallow Concentrated Flow, Overland Concentrated Flow Short Grass Pasture Kv= 7.0 fps
	1.7	150	0.0460	1.50		Shallow Concentrated Flow, Overland Concentrated Flow
_	2.8	225	0.0360	1.33		Short Grass Pasture Kv= 7.0 fps Shallow Concentrated Flow, Overland Concentrated Flow Short Grass Pasture Kv= 7.0 fps
	19.4	778	Total			

Subcatchment DB-A3: Drainage Basin A3



Prepared by Phillip Lewis Engineering

HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Subcatchment DB-A4: Drainage Basin A4


Runoff = 3.73 cfs @ 0.19 hrs, Volume= 3,355 cf, Depth= 1.01"

Routed to Link Pre: Pre Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 25-yr Duration=15 min, Inten=5.44 in/hr

_	Α	rea (sf)	С	Description	1	
		40,000	0.74			
40,000 100.00% Pervious Area					ervious Are	ea
	Tc (min)	Length (feet)	Slope (ft/ft)		Capacity (cfs)	Description
_	3.8	50	0.0390	0.22		Sheet Flow, Overland Sheet Flow Grass: Short n= 0.150 P2= 4.19"
	6.4	114	0.0530	0.30		Sheet Flow, Overland Sheet Flow
	0.9	91	0.0600	1.71		Grass: Short n= 0.150 P2= 4.19" Shallow Concentrated Flow, Overland Concentrated Flow Short Grass Pasture Kv= 7.0 fps
_	11.1	255	Total			·

Subcatchment DB-A4: Drainage Basin A4



Summary for Subcatchment DB-A5: Drainage Basin A5


Runoff = 2.96 cfs @ 0.09 hrs, Volume= 2,664 cf, Depth= 1.01"

Routed to Link Pre: Pre Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 25-yr Duration=15 min, Inten=5.44 in/hr

	Α	rea (sf)	С	Description)	
		31,762	0.74			
_		31,762		100.00% P	ervious Are	ea
	Tc (min)	Length (feet)	Slope (ft/ft)	,	Capacity (cfs)	Description
-	5.2	111	0.0850	0.35		Sheet Flow, Overland Sheet Flow
	0.2	23	0.0680	1.91		Grass: Short n= 0.150 P2= 4.19" Sheet Flow, Overland Sheet Flow Smooth surfaces n= 0.011 P2= 4.19"
	5 4	134	Total	•		

Subcatchment DB-A5: Drainage Basin A5



Summary for Subcatchment DB-A6: Drainage Basin A6


Runoff = 9.69 cfs @ 0.25 hrs, Volume= 8,719 cf, Depth= 0.80"

Routed to Link Pre: Pre Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 25-yr Duration=15 min, Inten=5.44 in/hr

	Aı	rea (sf)	С	Description	١	
-	1	30,999	0.74			
	1	30,999		100.00% P	ervious Are	ea
	Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
-	16.9	300	0.0330	0.30	, ,	Sheet Flow, Overland Sheet Flow
	2.0	150	0.0330	1.27		Grass: Short n= 0.150 P2= 4.19" Shallow Concentrated Flow, Overland Concentrated Flow Short Grass Pasture Kv= 7.0 fps
	18.9	450	Total			

Subcatchment DB-A6: Drainage Basin A6



AR - Little Rock 25-yr Duration=15 min, Inten=5.44 in/hr Printed 9/19/2023

Prepared by Phillip Lewis Engineering
HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Link Pre: Pre Development


Inflow Area = 831,534 sf, 0.00% Impervious, Inflow Depth = 0.88" for 25-yr event

Inflow = 67.62 cfs @ 0.25 hrs, Volume= 60,640 cf

Primary = 67.62 cfs @ 0.25 hrs, Volume= 60,640 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs

Link Pre: Pre Development



HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Subcatchment DB-A1: Drainage Basin A1


Runoff = 10.47 cfs @ 0.09 hrs, Volume= 9,422 cf, Depth= 1.11"

Routed to Link Pre: Pre Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 50-yr Duration=15 min, Inten=6.00 in/hr

	Α	rea (sf)	С	Description)	
	1	01,860	0.74			
101,860 100.00% Pervious Area					ervious Are	ea
	Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
•	5.0	415		1.38		Direct Entry, Overland Concentrated Flow (Min)

Subcatchment DB-A1: Drainage Basin A1



HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Subcatchment DB-A2: Drainage Basin A2


Runoff = 17.25 cfs @ 0.09 hrs, Volume= 15,521 cf, Depth= 1.11"

Routed to Link Pre: Pre Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 50-yr Duration=15 min, Inten=6.00 in/hr

_	Α	rea (sf)	С	Description		
	1	67,793	0.74			
	167,793 100.00% Pervious Area					ea
	Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
	5.0	402	, ,	1.34		Direct Entry, Overland Concentrated Flow (Min)

Subcatchment DB-A2: Drainage Basin A2



Prepared by Phillip Lewis Engineering

HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Subcatchment DB-A3: Drainage Basin A3


Runoff = 28.54 cfs @ 0.25 hrs, Volume= 25,684 cf, Depth= 0.86"

Routed to Link Pre: Pre Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 50-yr Duration=15 min, Inten=6.00 in/hr

_	Α	rea (sf)	С	Description]	
	3	59,120	0.74			
	359,120 100.00% Pervious Are				ervious Are	ea
	Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
_	13.7	300	0.0420	0.37	, ,	Sheet Flow, Overland Sheet Flow
						Range n= 0.130 P2= 4.19"
	1.2	103	0.0430	1.45		Shallow Concentrated Flow, Overland Concentrated Flow
	4 7	450	0.0400	4.50		Short Grass Pasture Kv= 7.0 fps
	1.7	150	0.0460	1.50		Shallow Concentrated Flow, Overland Concentrated Flow
	2.0	225	0.0260	1 22		Short Grass Pasture Kv= 7.0 fps
	2.8	225	0.0360	1.33		Shallow Concentrated Flow, Overland Concentrated Flow Short Grass Pasture Kv= 7.0 fps
_	10.1					Short Grass Fasture IV- 1.0 Ips
	19.4	778	Total			

Subcatchment DB-A3: Drainage Basin A3



Summary for Subcatchment DB-A4: Drainage Basin A4


Runoff = 4.11 cfs @ 0.19 hrs, Volume= 3,700 cf, Depth= 1.11"

Routed to Link Pre: Pre Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 50-yr Duration=15 min, Inten=6.00 in/hr

Α	rea (sf)	С	Description	1	
	40,000	0.74			
40,000 100.00% Pervious Area				ervious Are	ea
Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
3.8	50	0.0390	0.22		Sheet Flow, Overland Sheet Flow
6.4	114	0.0530	0.30		Grass: Short n= 0.150 P2= 4.19" Sheet Flow, Overland Sheet Flow
0.9	91	0.0600	1.71		Grass: Short n= 0.150 P2= 4.19" Shallow Concentrated Flow, Overland Concentrated Flow Short Grass Pasture Kv= 7.0 fps
11.1	255	Total			·

Subcatchment DB-A4: Drainage Basin A4



Summary for Subcatchment DB-A5: Drainage Basin A5


Runoff = 3.26 cfs @ 0.09 hrs, Volume= 2,938 cf, Depth= 1.11"

Routed to Link Pre: Pre Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 50-yr Duration=15 min, Inten=6.00 in/hr

	Α	rea (sf)	С	Description)	
		31,762	0.74			
		31,762		100.00% P	ervious Are	ea
	Tc (min)	Length (feet)	Slope (ft/ft)	,	Capacity (cfs)	Description
-	5.2	111	0.0850	0.35		Sheet Flow, Overland Sheet Flow
	0.2	23	0.0680	1.91		Grass: Short n= 0.150 P2= 4.19" Sheet Flow, Overland Sheet Flow Smooth surfaces n= 0.011 P2= 4.19"
	5 4	134	Total	•		

Subcatchment DB-A5: Drainage Basin A5



Summary for Subcatchment DB-A6: Drainage Basin A6


Runoff = 10.69 cfs @ 0.25 hrs, Volume= 9,617 cf, Depth= 0.88"

Routed to Link Pre: Pre Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 50-yr Duration=15 min, Inten=6.00 in/hr

	Aı	rea (sf)	С	Description	١	
-	1	30,999	0.74			
	1	30,999		100.00% P	ervious Are	ea
	Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
-	16.9	300	0.0330	0.30	, ,	Sheet Flow, Overland Sheet Flow
	2.0	150	0.0330	1.27		Grass: Short n= 0.150 P2= 4.19" Shallow Concentrated Flow, Overland Concentrated Flow Short Grass Pasture Kv= 7.0 fps
	18.9	450	Total			

Subcatchment DB-A6: Drainage Basin A6



AR - Little Rock 50-yr Duration=15 min, Inten=6.00 in/hr Printed 9/19/2023

Prepared by Phillip Lewis Engineering
HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Link Pre: Pre Development


Inflow Area = 831,534 sf, 0.00% Impervious, Inflow Depth = 0.97" for 50-yr event

Inflow = 74.58 cfs @ 0.25 hrs, Volume= 66,882 cf

Primary = 74.58 cfs @ 0.25 hrs, Volume= 66,882 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs

Link Pre: Pre Development



Summary for Subcatchment DB-A1: Drainage Basin A1


Runoff = 11.38 cfs @ 0.09 hrs, Volume= 10,239 cf, Depth= 1.21"

Routed to Link Pre: Pre Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 100-yr Duration=15 min, Inten=6.52 in/hr

_	Α	rea (sf)	С	Description	1	
	1	01,860	0.74			
	1	01,860		100.00% P	ervious Are	ea
	Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
	5.0	415		1.38		Direct Entry, Overland Concentrated Flow (Min)

Subcatchment DB-A1: Drainage Basin A1



HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Subcatchment DB-A2: Drainage Basin A2


Runoff = 18.74 cfs @ 0.09 hrs, Volume= 16,866 cf, Depth= 1.21"

Routed to Link Pre: Pre Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 100-yr Duration=15 min, Inten=6.52 in/hr

_	Α	rea (sf)	С	Description	1	
	1	67,793	0.74			
	1	67,793		100.00% P	ervious Are	ea
	Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
	5.0	402		1.34		Direct Entry, Overland Concentrated Flow (Min)

Subcatchment DB-A2: Drainage Basin A2



HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Subcatchment DB-A3: Drainage Basin A3


Runoff = 31.01 cfs @ 0.25 hrs, Volume= 27,910 cf, Depth= 0.93"

Routed to Link Pre: Pre Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 100-yr Duration=15 min, Inten=6.52 in/hr

Α	rea (sf)	С	Description)	
3	59,120	0.74			
3	59,120		100.00% P	ervious Are	ea
Tc (min)	Length (feet)	Slope (ft/ft)	,	Capacity (cfs)	Description
13.7	300	0.0420	0.37		Sheet Flow, Overland Sheet Flow
1.2	103	0.0430	1.45		Range n= 0.130 P2= 4.19" Shallow Concentrated Flow, Overland Concentrated Flow Short Grass Pasture Kv= 7.0 fps
1.7	150	0.0460	1.50		Shallow Concentrated Flow, Overland Concentrated Flow
2.8	225	0.0360	1.33		Short Grass Pasture Kv= 7.0 fps Shallow Concentrated Flow, Overland Concentrated Flow Short Grass Pasture Kv= 7.0 fps
19.4	778	Total			

Subcatchment DB-A3: Drainage Basin A3



HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Subcatchment DB-A4: Drainage Basin A4


Runoff = 4.47 cfs @ 0.19 hrs, Volume= 4,021 cf, Depth= 1.21"

Routed to Link Pre: Pre Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 100-yr Duration=15 min, Inten=6.52 in/hr

	Α	rea (sf)	С	Description	า	
		40,000	0.74			
		40,000		100.00% P	ervious Are	ea
	Tc (min)	Length (feet)	Slope (ft/ft)	•	Capacity (cfs)	Description
	3.8	50	0.0390	0.22		Sheet Flow, Overland Sheet Flow
	6.4	114	0.0530	0.30		Grass: Short n= 0.150 P2= 4.19" Sheet Flow, Overland Sheet Flow
	0.9	91	0.0600	1.71		Grass: Short n= 0.150 P2= 4.19" Shallow Concentrated Flow, Overland Concentrated Flow Short Grass Pasture Kv= 7.0 fps
-	11 1	255	Total			

Subcatchment DB-A4: Drainage Basin A4



Summary for Subcatchment DB-A5: Drainage Basin A5


Runoff = 3.55 cfs @ 0.09 hrs, Volume= 3,193 cf, Depth= 1.21"

Routed to Link Pre: Pre Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 100-yr Duration=15 min, Inten=6.52 in/hr

_	Α	rea (sf)	С	Description	Ì	
_		31,762	0.74			
		31,762		100.00% P	ervious Are	ea
	Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
-	5.2	111	0.0850	0.35	,	Sheet Flow, Overland Sheet Flow
	0.2	23	0.0680	1.91		Grass: Short n= 0.150 P2= 4.19" Sheet Flow, Overland Sheet Flow Smooth surfaces n= 0.011 P2= 4.19"
	5.4	134	Total			

Subcatchment DB-A5: Drainage Basin A5



HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Subcatchment DB-A6: Drainage Basin A6


Runoff = 11.61 cfs @ 0.25 hrs, Volume= 10,450 cf, Depth= 0.96"

Routed to Link Pre: Pre Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 100-yr Duration=15 min, Inten=6.52 in/hr

	Aı	rea (sf)	С	Description	١	
-	1	30,999	0.74			
	1	30,999		100.00% P	ervious Are	ea
	Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
-	16.9	300	0.0330	0.30	, ,	Sheet Flow, Overland Sheet Flow
	2.0	150	0.0330	1.27		Grass: Short n= 0.150 P2= 4.19" Shallow Concentrated Flow, Overland Concentrated Flow Short Grass Pasture Kv= 7.0 fps
	18.9	450	Total			

Subcatchment DB-A6: Drainage Basin A6



AR - Little Rock 100-yr Duration=15 min, Inten=6.52 in/hr Printed 9/19/2023

Prepared by Phillip Lewis Engineering
HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Link Pre: Pre Development


Inflow Area = 831,534 sf, 0.00% Impervious, Inflow Depth = 1.05" for 100-yr event


Inflow = 81.05 cfs @ 0.25 hrs, Volume= 72,679 cf

Primary = 81.05 cfs @ 0.25 hrs, Volume= 72,679 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs

Link Pre: Pre Development





HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC


Summary for Subcatchment DB-B1: Drainage Basin B1

Runoff = 10.52 cfs @ 0.09 hrs, Volume= 9,468 cf, Depth= 0.87" Routed to Pond 1P : Regional Detention Basin

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 2-yr Duration=15 min, Inten=3.54 in/hr

	Α	rea (sf)	С	Description	1	
_	1	30,996	0.98			
	1	30,996		100.00% Ir	npervious A	Area
	Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
	5.0					Direct Entry

Subcatchment DB-B1: Drainage Basin B1



HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Subcatchment DB-B2: Drainage Basin B2


Runoff = 8.31 cfs @ 0.09 hrs, Volume= 7,476 cf, Depth= 0.82" Routed to Pond 1P : Regional Detention Basin

Dunoff by Potional mathed Disa/Fall=1 0/1 0 yTa Time Span-

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 2-yr Duration=15 min, Inten=3.54 in/hr

	Α	rea (sf)	С	Description					
_		87,200	0.98						
_		21,800	0.74						
	1	109,000 0.93 Weighted Average							
		21,800		20.00% Pe	rvious Area	ea			
		87,200		80.00% Im	pervious Aı	Area			
	Тс	Length	Slope	Velocity	Capacity	Description			
	(min)	(feet)	(ft/ft)	•	(cfs)	·			
-		(ieet)	(11/11)	(10/560)	(CIS)				
	5.0					Direct Entry.			

Subcatchment DB-B2: Drainage Basin B2



HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Subcatchment DB-B3: Drainage Basin B3


Runoff = 42.28 cfs @ 0.25 hrs, Volume= 38,050 cf, Depth= 0.82" Routed to Pond 1P : Regional Detention Basin

3

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 2-yr Duration=15 min, Inten=3.54 in/hr

_	Aı	rea (sf)	С	Description					
	4	43,807	0.98						
_	1	10,952	0.74						
554,759 0.93 Weighted Average									
	110,952			20.00% Pervious Area					
	4	43,807		80.00% Im	pervious Aı	Area			
	Тс	Length	Slope	Velocity	Capacity	Description			
	(min)	(feet)	(ft/ft)	,	(cfs)	·			
	15.0					Direct Entry.			

Subcatchment DB-B3: Drainage Basin B3



HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Subcatchment DB-B4: Drainage Basin B4


Runoff = 2.96 cfs @ 0.09 hrs, Volume= 2,661 cf, Depth= 0.82"

Routed to Link Post: Post Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 2-yr Duration=15 min, Inten=3.54 in/hr

A	rea (sf)	С	Description					
	31,042	0.98						
	7,760	0.74						
	38,802	0.93 Weighted Average						
	7,760	,760 20.00% Pervious Area						
	31,042		80.00% Im	pervious Aı	rea			
_		01			5			
Tc	Length	Slope	,	Capacity	Description			
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)				
5.0					Direct Entry, 15			

Subcatchment DB-B4: Drainage Basin B4



Prepared by Phillip Lewis Engineering

HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Pond 1P: Regional Detention Basin

Inflow Area = 794,755 sf, 83.30% Impervious, Inflow Depth = 0.83" for 2-yr event

Inflow 61.22 cfs @ 0.25 hrs, Volume= 54.993 cf

Outflow 22.83 cfs @ 0.37 hrs, Volume= 51,485 cf, Atten= 63%, Lag= 7.0 min

22.83 cfs @ Primary 0.37 hrs, Volume= 51,485 cf

Routed to Link Post: Post Development

Secondary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routed to Link Post: Post Development

Routing by Stor-Ind method, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs

Peak Elev= 385.28' @ 0.37 hrs Storage= 33,530 cf

Plug-Flow detention time= 27.7 min calculated for 51,314 cf (93% of inflow)

Center-of-Mass det. time= 27.3 min (40.8 - 13.5)

Volume	Invert Av	/ail.Storage	Storage Description
#1	382.00'	64,856 cf	Custom Stage Data Listed below
Elevation (feet)	Cum.Store (cubic-feet	_	
382.00	,	Ō	
383.00	1,680	6	
384.00	11,04	5	
385.00	25,74	3	
386.00	53,76	4	
387.00	64,850	6	

Device	Routing	Invert	Outlet Devices
#1	Primary	382.00'	24.0" Round RCP_Round 24"
	·		L= 20.0' RCP, square edge headwall, Ke= 0.500
			Inlet / Outlet Invert= 382.00' / 381.00' S= 0.0500 '/' Cc= 0.900
			n= 0.013 Concrete pipe, bends & connections, Flow Area= 3.14 sf
#2	Secondary	386.50'	15.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s)
#3	Device 1	384.00'	15.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s)
#4	Device 1	382.00'	6.0" Vert. Orifice/Grate C= 0.600 Limited to weir flow at low heads

Primary OutFlow Max=22.83 cfs @ 0.37 hrs HW=385.28' (Free Discharge)


_1=RCP_Round 24" (Inlet Controls 22.83 cfs @ 7.27 fps)

-3=Sharp-Crested Rectangular Weir (Passes < 69.62 cfs potential flow)


-4=Orifice/Grate (Passes < 1.65 cfs potential flow)

Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=382.00' (Free Discharge) **—2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)

Pond 1P: Regional Detention Basin



Pond 1P: Regional Detention Basin



Stage-Area-Storage for Pond 1P: Regional Detention Basin

		ı <u>-</u>	
Elevation	Storage	Elevation	Storage
(feet)	(cubic-feet)	(feet)	(cubic-feet)
382.00	0	384.60	19,866
382.05	84	384.65	20,601
382.10	169	384.70	21,336
382.15	253	384.75	22,071
382.20	337	384.80	22,806
382.25	422	384.85	23,541
382.30	506	384.90	24,276
382.35	590	384.95	25,011
382.40	674	385.00	25,746
382.45	759	385.05	27,147
382.50	843	385.10	28,548
382.55	927	385.15	29,949
382.60	1,012	385.20	31,350
382.65	1,096	385.25	32,751
382.70	1,180	385.30	34,151
382.75	1,265	385.35	35,552
382.80	1,349	385.40	36,953
382.85	1,433	385.45	38,354
382.90	1,517	385.50	39,755
382.95	1,602	385.55	41,156
383.00	1,686	385.60	42,557
383.05	2,154	385.65	43,958
383.10	2,622	385.70	45,359
383.15	3,090	385.75	46,760
383.20	3,558	385.80	48,160
383.25	4,026	385.85	49,561
383.30	4,494	385.90	50,962
383.35	4,962	385.95	52,363 52,764
383.40	5,430	386.00	53,764
383.45	5,898 6.366	386.05	54,319 54,973
383.50	6,366	386.10	54,873
383.55	6,833 7,301	386.15	55,428
383.60	7,301	386.20	55,982 56,537
383.65	7,769	386.25 386.30	56,537 57,002
383.70 383.75	8,237 8,705	386.35	57,092 57,646
383.80	8,705 9,173	386.40	57,646 58 201
383.85	9,173 9,641	386.45	58,201 58,755
	10,109		59,310
383.90 383.95	10,109	386.50 386.55	59,865
384.00	11,045	386.60	60,419
384.05	11,780	386.65	60,974
384.10	12,515	386.70	61,528
384.15	13,250	386.75	62,083
384.20	13,985	386.80	62,638
384.25	14,720	386.85	63,192
384.30	15,455	386.90	63,747
384.35	16,190	386.95	64,301
384.40	16,190	387.00	64,856
384.45	17,660	307.00	0-1,000
384.50	18,396		
384.55	19,131		
JU+.JJ	13,131		

HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Link Post: Post Development


Inflow Area = 833,557 sf, 83.14% Impervious, Inflow Depth > 0.78" for 2-yr event

Inflow = 24.52 cfs @ 0.25 hrs, Volume= 54,147 cf

Primary = 24.52 cfs @ 0.25 hrs, Volume= 54,147 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs

Link Post: Post Development



Prepared by Phillip Lewis Engineering
HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC


Summary for Subcatchment DB-B1: Drainage Basin B1

Runoff = 12.48 cfs @ 0.09 hrs, Volume= 11,233 cf, Depth= 1.03" Routed to Pond 1P : Regional Detention Basin

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 5-yr Duration=15 min, Inten=4.20 in/hr

_	Α	rea (sf)	С	Description	1	
	1	30,996	0.98			
_	1	30,996		100.00% lr	npervious A	Area
		Length	Slope	,		Description
_	(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	
	5.0					Direct Entry

Subcatchment DB-B1: Drainage Basin B1



HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC


Summary for Subcatchment DB-B2: Drainage Basin B2

Runoff = 9.86 cfs @ 0.09 hrs, Volume= 8,870 cf, Depth= 0.98" Routed to Pond 1P : Regional Detention Basin

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 5-yr Duration=15 min, Inten=4.20 in/hr

	Α	rea (sf)	С	Description				
_		87,200	0.98					
_		21,800	0.74					
	1	09,000	0.93	Weighted A	Average			
		21,800		20.00% Pervious Area				
		87,200		80.00% Im	pervious Aı	Area		
	Тс	Length	Slope	Velocity	Capacity	Description		
	(min)	(feet)	(ft/ft)	•	(cfs)	·		
-		(ieet)	(11/11)	(11/560)	(CIS)			
	5.0					Direct Entry.		

Subcatchment DB-B2: Drainage Basin B2



Prepared by Phillip Lewis Engineering
HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC


Summary for Subcatchment DB-B3: Drainage Basin B3

Runoff = 50.16 cfs @ 0.25 hrs, Volume= 45,144 cf, Depth= 0.98" Routed to Pond 1P : Regional Detention Basin

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 5-yr Duration=15 min, Inten=4.20 in/hr

_	Aı	rea (sf)	С	Description	1	
Ī	4	43,807	0.98			
	1	10,952	0.74			
	5	54,759	0.93	Weighted A	Average	
	1	10,952		20.00% Pe	rvious Area	ea
	4	43,807		80.00% Im	pervious Aı	Area
	Тс	Length	Slope	Velocity	Capacity	Description
	(min)	(feet)	(ft/ft)	,	(cfs)	·
	15.0					Direct Entry.

Subcatchment DB-B3: Drainage Basin B3



HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Subcatchment DB-B4: Drainage Basin B4


Runoff = 3.51 cfs @ 0.09 hrs, Volume= 3,158 cf, Depth= 0.98"

Routed to Link Post: Post Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 5-yr Duration=15 min, Inten=4.20 in/hr

	Α	rea (sf)	С	Description	1	
		31,042	0.98			
		7,760	0.74			
		38,802	0.93	Weighted A	Average	
		7,760		20.00% Pervious Area		
		31,042		80.00% Im	pervious Aı	rea
	Тс	Length	Slope	Velocity	Capacity	Description
(r	min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	
	5.0					Direct Entry, 15

Subcatchment DB-B4: Drainage Basin B4



Prepared by Phillip Lewis Engineering

HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Pond 1P: Regional Detention Basin

Inflow Area = 794,755 sf, 83.30% Impervious, Inflow Depth = 0.99" for 5-yr event

Inflow 72.63 cfs @ 0.25 hrs. Volume= 65.246 cf

Outflow 0.38 hrs, Volume= 24.13 cfs @ 61,419 cf, Atten= 67%, Lag= 7.9 min

Primary 24.13 cfs @ 0.38 hrs, Volume= 61,419 cf

Routed to Link Post: Post Development

Secondary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routed to Link Post: Post Development

Routing by Stor-Ind method, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs

Peak Elev= 385.54' @ 0.38 hrs Storage= 41,013 cf

Plug-Flow detention time= 27.2 min calculated for 61,215 cf (94% of inflow)

Center-of-Mass det. time= 26.9 min (40.3 - 13.5)

Volume	Invert Av	/ail.Storage	Storage Description
#1	382.00'	64,856 cf	Custom Stage Data Listed below
Elevation (feet)	Cum.Stor	_	
382.00		Ō	
383.00	1,68	6	
384.00	11,04	5	
385.00	25,74	6	
386.00	53,76	4	
387.00	64,85	6	

Device	Routing	Invert	Outlet Devices
#1	Primary	382.00'	24.0" Round RCP_Round 24"
			L= 20.0' RCP, square edge headwall, Ke= 0.500
			Inlet / Outlet Invert= 382.00' / 381.00' S= 0.0500 '/' Cc= 0.900
			n= 0.013 Concrete pipe, bends & connections, Flow Area= 3.14 sf
#2	Secondary	386.50'	15.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s)
#3	Device 1	384.00'	15.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s)
#4	Device 1	382.00'	6.0" Vert. Orifice/Grate C= 0.600 Limited to weir flow at low heads

Primary OutFlow Max=24.13 cfs @ 0.38 hrs HW=385.54' (Free Discharge)


_1=RCP_Round 24" (Inlet Controls 24.13 cfs @ 7.68 fps)

3=Sharp-Crested Rectangular Weir (Passes < 92.24 cfs potential flow)


-4=Orifice/Grate (Passes < 1.72 cfs potential flow)

Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=382.00' (Free Discharge) 2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)

Pond 1P: Regional Detention Basin



Pond 1P: Regional Detention Basin



Stage-Area-Storage for Pond 1P: Regional Detention Basin

	o. 1		.
Elevation	Storage	Elevation	Storage
(feet)	(cubic-feet)	(feet)	(cubic-feet)
382.00	0	384.60	19,866
382.05	84	384.65	20,601
382.10	169	384.70	21,336
382.15	253	384.75	22,071
382.20	337	384.80	22,806
382.25	422	384.85	23,541
382.30	506	384.90	24,276
382.35	590	384.95	25,011
382.40	674	385.00	25,746
382.45	759	385.05	27,147
382.50	843	385.10	28,548
382.55	927	385.15	29,949
382.60	1,012	385.20	31,350
382.65	1,096	385.25	32,751
382.70	1,180	385.30	34,151
382.75	1,265	385.35	35,552
382.80	1,349	385.40	36,953
382.85	1,433	385.45	38,354
382.90	1,517	385.50	39,755
382.95 383.00	1,602 1,686	385.55 385.60	41,156
383.05	2,154	385.65	42,557 43,958
383.10	2,134	385.70	45,359
383.15	3,090	385.75	46,760
383.20	3,558	385.80	48,160
383.25	4,026	385.85	49,561
383.30	4,494	385.90	50,962
383.35	4,962	385.95	52,363
383.40	5,430	386.00	53,764
383.45	5,898	386.05	54,319
383.50	6,366	386.10	54,873
383.55	6,833	386.15	55,428
383.60	7,301	386.20	55,982
383.65	7,769	386.25	56,537
383.70	8,237	386.30	57,092
383.75	8,705	386.35	57,646
383.80	9,173	386.40	58,201
383.85	9,641	386.45	58,755
383.90	10,109	386.50	59,310
383.95	10,577	386.55	59,865
384.00	11,045	386.60	60,419
384.05	11,780	386.65	60,974
384.10	12,515	386.70	61,528
384.15	13,250	386.75	62,083
384.20	13,985	386.80	62,638
384.25	14,720	386.85	63,192
384.30	15,455	386.90	63,747
384.35	16,190	386.95	64,301
384.40	16,925	387.00	64,856
384.45	17,660		
384.50	18,396		
384.55	19,131		

HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Link Post: Post Development


Inflow Area = 833,557 sf, 83.14% Impervious, Inflow Depth > 0.93" for 5-yr event

Inflow = 25.96 cfs @ 0.25 hrs, Volume= 64,577 cf

Primary = 25.96 cfs @ 0.25 hrs, Volume= 64,577 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs

Link Post: Post Development



HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC


Summary for Subcatchment DB-B1: Drainage Basin B1

Runoff = 14.15 cfs @ 0.09 hrs, Volume= 12,731 cf, Depth= 1.17" Routed to Pond 1P : Regional Detention Basin

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 10-yr Duration=15 min, Inten=4.76 in/hr

	Α	rea (sf)	С	Description	1	
_	1	30,996	0.98			
	130,996 100.00% Impervious A			100.00% Ir	npervious A	Area
	Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
	5.0					Direct Entry

Subcatchment DB-B1: Drainage Basin B1



HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC


Summary for Subcatchment DB-B2: Drainage Basin B2

Runoff = 11.17 cfs @ 0.09 hrs, Volume= 10,053 cf, Depth= 1.11" Routed to Pond 1P : Regional Detention Basin

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 10-yr Duration=15 min, Inten=4.76 in/hr

	Α	rea (sf)	С	Description	Description				
		87,200	0.98						
		21,800	0.74						
	1	109,000	0.93	Weighted /	Weighted Average				
		21,800		20.00% Pervious Area					
		87,200		80.00% Im	pervious A	Area			
	Тс	Length	Slope	Velocity	Capacity	Description			
	(min)	(feet)	(ft/ft)	,	(cfs)	·			
_	5.0	(1001)	(14,14)	(14000)	(0.0)	Direct Entry.			

Subcatchment DB-B2: Drainage Basin B2



HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC


Summary for Subcatchment DB-B3: Drainage Basin B3

Runoff = 56.85 cfs @ 0.25 hrs, Volume= 51,163 cf, Depth= 1.11" Routed to Pond 1P : Regional Detention Basin

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 10-yr Duration=15 min, Inten=4.76 in/hr

	A	rea (sf)	С	Description	escription				
Ī	4	43,807	0.98						
_	1	10,952	0.74						
	5	554,759 0.93 Weighted Average							
	110,952			20.00% Pervious Area					
	443,807			80.00% Im	pervious Aı	Area			
	Tc	Length	Slope	,	Capacity	·			
_	(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)				
	15.0					Direct Entry.			

Subcatchment DB-B3: Drainage Basin B3



Summary for Subcatchment DB-B4: Drainage Basin B4


Runoff = 3.98 cfs @ 0.09 hrs, Volume= 3,579 cf, Depth= 1.11"

Routed to Link Post: Post Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 10-yr Duration=15 min, Inten=4.76 in/hr

	rea (sf)	С	Description					
	31,042	0.98						
	7,760	0.74						
	38,802	0.93	Weighted Average					
	7,760		20.00% Pervious Area					
	31,042		80.00% Im	pervious Aı	rea			
_		01			5			
Tc	J	Slope	,	Capacity	Description			
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)				
5.0					Direct Entry, 15			

Subcatchment DB-B4: Drainage Basin B4



Summerwood Gym 3

Prepared by Phillip Lewis Engineering

HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Pond 1P: Regional Detention Basin

Inflow Area = 794,755 sf, 83.30% Impervious, Inflow Depth = 1.12" for 10-yr event

Inflow 82.31 cfs @ 0.25 hrs. Volume= 73.946 cf

Outflow 0.39 hrs, Volume= 25.23 cfs @ 69,849 cf, Atten= 69%, Lag= 8.5 min

25.23 cfs @ Primary 0.39 hrs, Volume= 69,849 cf

Routed to Link Post: Post Development

0.00 hrs, Volume= Secondary = 0.00 cfs @ 0 cf

Routed to Link Post: Post Development

Routing by Stor-Ind method, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs

Peak Elev= 385.78' @ 0.39 hrs Storage= 47,655 cf

Plug-Flow detention time= 27.4 min calculated for 69,617 cf (94% of inflow)

Center-of-Mass det. time= 27.1 min (40.5 - 13.5)

Volume	Invert Av	ail.Storage	Storage Description
#1	382.00'	64,856 cf	Custom Stage Data Listed below
Elevation (feet)	Cum.Store		
382.00	(_	
383.00	1,686	3	
384.00	11,045	5	
385.00	25,746	3	
386.00	53,764	1	
387.00	64,856	6	

Device	Routing	Invert	Outlet Devices
#1	Primary	382.00'	24.0" Round RCP_Round 24"
	•		L= 20.0' RCP, square edge headwall, Ke= 0.500
			Inlet / Outlet Invert= 382.00' / 381.00' S= 0.0500 '/' Cc= 0.900
			n= 0.013 Concrete pipe, bends & connections, Flow Area= 3.14 sf
#2	Secondary	386.50'	15.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s)
#3	Device 1	384.00'	15.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s)
#4	Device 1	382.00'	6.0" Vert. Orifice/Grate C= 0.600 Limited to weir flow at low heads

Primary OutFlow Max=25.23 cfs @ 0.39 hrs HW=385.78' (Free Discharge)

_1=RCP_Round 24" (Inlet Controls 25.23 cfs @ 8.03 fps)


-3=Sharp-Crested Rectangular Weir (Passes < 113.89 cfs potential flow)

-4=Orifice/Grate (Passes < 1.78 cfs potential flow)


Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=382.00' (Free Discharge) 2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)

HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Pond 1P: Regional Detention Basin



Pond 1P: Regional Detention Basin



Summerwood Gym 3 AR - Little Rock 10-yr Du Prepared by Phillip Lewis Engineering HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Stage-Area-Storage for Pond 1P: Regional Detention Basin

	- . 1		
Elevation	Storage	Elevation	Storage
(feet)	(cubic-feet)	(feet)	(cubic-feet)
382.00	0	384.60	19,866
382.05	84	384.65	20,601
382.10	169	384.70	21,336
382.15	253	384.75	22,071
382.20	337	384.80	22,806
382.25	422	384.85	23,541
382.30	506	384.90	24,276
382.35	590	384.95	25,011
382.40	674	385.00	25,746
382.45	759	385.05	27,147
382.50	843	385.10	28,548
382.55	927	385.15	29,949
382.60	1,012	385.20	31,350
382.65	1,096	385.25	32,751
382.70	1,180	385.30	34,151
382.75	1,265	385.35	35,552
382.80	1,349	385.40	36,953
382.85	· ·	385.45	
	1,433		38,354
382.90	1,517	385.50	39,755
382.95	1,602	385.55	41,156
383.00	1,686	385.60	42,557
383.05	2,154	385.65	43,958
383.10	2,622	385.70	45,359
383.15	3,090	385.75	46,760
383.20	3,558	385.80	48,160
383.25	4,026	385.85	49,561
383.30	4,494	385.90	50,962
383.35	4,962	385.95	52,363
383.40	5,430	386.00	53,764
383.45	5,898	386.05	54,319
383.50	6,366	386.10	54,873
383.55	6,833	386.15	55,428
383.60	7,301	386.20	55,982
383.65	7,769	386.25	56,537
383.70	8,237	386.30	57,092
383.75	8,705	386.35	57,646
383.80	9,173	386.40	58,201
383.85	9,641	386.45	58,755
383.90	10,109	386.50	59,310
383.95	10,577	386.55	59,865
384.00	11,045	386.60	60,419
384.05	11,780	386.65	60,974
384.10	12,515	386.70	61,528
384.15	13,250	386.75	62,083
384.20	13,985	386.80	62,638
384.25	14,720	386.85	63,192
384.30	15,455	386.90	63,747
384.35	16,190	386.95	64,301
384.40	16,925	387.00	64,856
384.45	17,660	357.00	0-1,000
384.50	18,396		
384.55	19,131		
001.00	70, 101		
	ļ	1	

HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Link Post: Post Development


Inflow Area = 833,557 sf, 83.14% Impervious, Inflow Depth > 1.06" for 10-yr event

Inflow = 27.20 cfs @ 0.25 hrs, Volume= 73,428 cf

Primary = 27.20 cfs @ 0.25 hrs, Volume= 73,428 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs

Link Post: Post Development




Summary for Subcatchment DB-B1: Drainage Basin B1

Runoff = 16.17 cfs @ 0.09 hrs, Volume= 14,549 cf, Depth= 1.33" Routed to Pond 1P : Regional Detention Basin

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 25-yr Duration=15 min, Inten=5.44 in/hr

Ar	ea (sf)	С	Description	1	
1:	30,996	0.98			
1:	30,996	100.00% Impervious A			Area
	Length	Slope	,	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	
5.0					Direct Entry,

Subcatchment DB-B1: Drainage Basin B1




Summary for Subcatchment DB-B2: Drainage Basin B2

Runoff = 12.77 cfs @ 0.09 hrs, Volume= 11,489 cf, Depth= 1.26" Routed to Pond 1P : Regional Detention Basin

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 25-yr Duration=15 min, Inten=5.44 in/hr

	Α	rea (sf)	С	Description	Description				
_		87,200	0.98						
_		21,800	0.74						
	1	109,000	0.93	Weighted A	Weighted Average				
		21,800		20.00% Pe	rvious Area	ea			
		87,200		80.00% Im	pervious Aı	Area			
	Тс	Length	Slope	Velocity	Capacity	Description			
	(min)	(feet)	(ft/ft)	•	(cfs)	·			
-		(ieet)	(11/11)	(10/560)	(CIS)				
	5.0					Direct Entry.			

Subcatchment DB-B2: Drainage Basin B2




Summary for Subcatchment DB-B3: Drainage Basin B3

Runoff = 64.97 cfs @ 0.25 hrs, Volume= 58,472 cf, Depth= 1.26" Routed to Pond 1P : Regional Detention Basin

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 25-yr Duration=15 min, Inten=5.44 in/hr

	A	rea (sf)	С	Description	escription				
Ī	4	43,807	0.98						
_	1	10,952	0.74						
	5	554,759 0.93 Weighted Average							
	110,952			20.00% Pervious Area					
	443,807			80.00% Im	pervious Aı	Area			
	Tc	Length	Slope	,	Capacity	·			
_	(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)				
	15.0					Direct Entry.			

Subcatchment DB-B3: Drainage Basin B3



HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Subcatchment DB-B4: Drainage Basin B4


Runoff = 4.54 cfs @ 0.09 hrs, Volume= 4,090 cf, Depth= 1.26"

Routed to Link Post: Post Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 25-yr Duration=15 min, Inten=5.44 in/hr

Α	rea (sf)	С	Description	1				
	31,042	0.98						
	7,760	0.74						
	38,802	0.93	Weighted A	Weighted Average				
	7,760		20.00% Pervious Area					
	31,042		80.00% Im	pervious Aı	rea			
Тс	Length	Slope	Velocity	Capacity	Description			
 (min)	(feet)	(ft/ft)	(ft/sec)	(cfs)				
5.0					Direct Entry 15			

Subcatchment DB-B4: Drainage Basin B4



Summerwood Gym 3

Prepared by Phillip Lewis Engineering

HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Pond 1P: Regional Detention Basin

Inflow Area = 794,755 sf, 83.30% Impervious, Inflow Depth = 1.28" for 25-yr event

Inflow = 94.07 cfs @ 0.25 hrs, Volume= 84,509 cf

Outflow = 27.02 cfs @ 0.40 hrs, Volume= 80,097 cf, Atten= 71%, Lag= 8.9 min

Primary = 27.02 cfs @ 0.40 hrs, Volume= 80,097 cf

Routed to Link Post: Post Development

Secondary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routed to Link Post: Post Development

Routing by Stor-Ind method, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs

Peak Elev= 386.19' @ 0.40 hrs Storage= 55,881 cf

Plug-Flow detention time= 28.0 min calculated for 79,831 cf (94% of inflow)

Center-of-Mass det. time= 27.7 min (41.1 - 13.5)

64.856

387.00

Volume	Invert A	Avail.Storage	Storage Description
#1	382.00'	64,856 cf	Custom Stage Data Listed below
Elevation (feet)	Cum.Sto (cubic-fe		
382.00	•	0	
383.00	1,6	86	
384.00	11,0	45	
385.00	25,7	46	
386.00	53,7	64	

Device	Routing	Invert	Outlet Devices
#1	Primary	382.00'	24.0" Round RCP_Round 24"
	•		L= 20.0' RCP, square edge headwall, Ke= 0.500
			Inlet / Outlet Invert= 382.00' / 381.00' S= 0.0500 '/' Cc= 0.900
			n= 0.013 Concrete pipe, bends & connections, Flow Area= 3.14 sf
#2	Secondary	386.50'	15.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s)
#3	Device 1	384.00'	15.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s)
#4	Device 1	382 00'	6.0" Vert Orifice/Grate C= 0.600 Limited to weir flow at low heads

Primary OutFlow Max=27.02 cfs @ 0.40 hrs HW=386.19' (Free Discharge)

1=RCP_Round 24" (Inlet Controls 27.02 cfs @ 8.60 fps)


3=Sharp-Crested Rectangular Weir (Passes < 154.31 cfs potential flow)

-4=Orifice/Grate (Passes < 1.88 cfs potential flow)


Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=382.00' (Free Discharge) 2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)

HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Pond 1P: Regional Detention Basin



Pond 1P: Regional Detention Basin



Summerwood Gym 3 AR - Little Rock 25-yr Du Prepared by Phillip Lewis Engineering HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Stage-Area-Storage for Pond 1P: Regional Detention Basin

□lavatia.	Ctonone		Ctamana
Elevation (fact)	Storage	Elevation	Storage
(feet)	(cubic-feet)	(feet)	(cubic-feet)
382.00	0	384.60	19,866
382.05	84	384.65	20,601
382.10	169	384.70	21,336
382.15	253	384.75	22,071
382.20	337	384.80	22,806
382.25	422	384.85	23,541
382.30	506	384.90	24,276
382.35	590 674	384.95	25,011
382.40	674	385.00	25,746
382.45	759	385.05	27,147
382.50	843	385.10	28,548
382.55	927	385.15	29,949
382.60	1,012	385.20	31,350
382.65	1,096	385.25	32,751
382.70	1,180	385.30	34,151
382.75	1,265	385.35	35,552
382.80	1,349	385.40	36,953
382.85	1,433	385.45	38,354
382.90	1,517	385.50	39,755
382.95	1,602	385.55	41,156
383.00	1,686	385.60	42,557
383.05	2,154	385.65	43,958
383.10	2,622	385.70	45,359
383.15	3,090	385.75	46,760
383.20	3,558	385.80	48,160
383.25	4,026	385.85	49,561
383.30	4,494	385.90	50,962
383.35	4,962	385.95	52,363
383.40	5,430	386.00	53,764
383.45	5,898	386.05	54,319
383.50	6,366	386.10	54,873
383.55	6,833	386.15	55,428
383.60	7,301	386.20	55,982
383.65	7,769	386.25	56,537
383.70	8,237	386.30	57,092
383.75	8,705	386.35	57,646
383.80	9,173	386.40	58,201
383.85	9,641	386.45	58,755
383.90	10,109	386.50	59,310
383.95	10,577	386.55	59,865
384.00	11,045	386.60	60,419
384.05	11,780	386.65	60,974
384.10	12,515	386.70	61,528
384.15	13,250	386.75	62,083
384.20	13,985	386.80	62,638
384.25	14,720	386.85	63,192
384.30	15,455	386.90	63,747
384.35	16,190	386.95	64,301
384.40	16,925	387.00	64,856
384.45	17,660		
384.50	18,396		
384.55	19,131		
		I	

HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Link Post: Post Development


Inflow Area = 833,557 sf, 83.14% Impervious, Inflow Depth > 1.21" for 25-yr event

Inflow = 28.69 cfs @ 0.25 hrs, Volume= 84,187 cf

Primary = 28.69 cfs @ 0.25 hrs, Volume= 84,187 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs

Link Post: Post Development



HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC


Summary for Subcatchment DB-B1: Drainage Basin B1

Runoff = 17.83 cfs @ 0.09 hrs, Volume= 16,047 cf, Depth= 1.47" Routed to Pond 1P : Regional Detention Basin

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 50-yr Duration=15 min, Inten=6.00 in/hr

Ar	ea (sf)	С	Description	1	
1:	30,996	0.98			
130,996 100.00% Imperviou			100.00% Ir	npervious A	Area
	Length	Slope	,	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	
5.0					Direct Entry,

Subcatchment DB-B1: Drainage Basin B1



HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC


Summary for Subcatchment DB-B2: Drainage Basin B2

Runoff = 14.08 cfs @ 0.09 hrs, Volume= 12,671 cf, Depth= 1.40" Routed to Pond 1P : Regional Detention Basin

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 50-yr Duration=15 min, Inten=6.00 in/hr

	Α	rea (sf)	С	Description	Description				
_		87,200	0.98						
_		21,800	0.74						
	1	109,000	0.93	Weighted Average					
		21,800		20.00% Pervious Area					
	87,200 80.00% Impervious Ar				pervious Aı	Area			
	Тс	Length	Slope	Velocity	Capacity	Description			
	(min)	(feet)	(ft/ft)	•	(cfs)	·			
-		(ieet)	(11/11)	(10/560)	(CIS)				
	5.0					Direct Entry.			

Subcatchment DB-B2: Drainage Basin B2



HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC


Summary for Subcatchment DB-B3: Drainage Basin B3

Runoff = 71.66 cfs @ 0.25 hrs, Volume= 64,491 cf, Depth= 1.40" Routed to Pond 1P : Regional Detention Basin

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 50-yr Duration=15 min, Inten=6.00 in/hr

	A	rea (sf)	С	Description	Description					
Ī	4	43,807	0.98							
_	1	10,952	0.74							
554,759 0.93 Weig				Weighted A	Average					
	110,952			20.00% Pervious Area						
	443,807			80.00% Im	pervious Aı	Area				
	Tc	Length	Slope	,	Capacity	·				
_	(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)					
	15.0					Direct Entry.				

Subcatchment DB-B3: Drainage Basin B3



HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Subcatchment DB-B4: Drainage Basin B4


Runoff = 5.01 cfs @ 0.09 hrs, Volume= 4,511 cf, Depth= 1.40"

Routed to Link Post: Post Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 50-yr Duration=15 min, Inten=6.00 in/hr

A	rea (sf)	С	Description				
	31,042	0.98					
	7,760	0.74					
	38,802	0.93	Weighted Average				
	7,760		20.00% Pe	rvious Area	a		
	31,042		80.00% Im	pervious Aı	rea		
-		01		0 "	5		
Tc	Length	Slope	,	Capacity	Description		
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)			
5.0					Direct Entry, 15		

Subcatchment DB-B4: Drainage Basin B4



Summerwood Gym 3

Prepared by Phillip Lewis Engineering

HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Pond 1P: Regional Detention Basin

Inflow Area = 794,755 sf, 83.30% Impervious, Inflow Depth = 1.41" for 50-yr event

Inflow 103.76 cfs @ 0.25 hrs. Volume= 93.209 cf

33.94 cfs @ 0.38 hrs, Volume= 88,612 cf, Atten= 67%, Lag= 8.0 min Outflow

Primary 29.14 cfs @ 0.38 hrs, Volume= 87,226 cf

Routed to Link Post: Post Development

Secondary = 4.79 cfs @ 0.38 hrs, Volume= 1,386 cf

Routed to Link Post: Post Development

Routing by Stor-Ind method, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs

Peak Elev= 386.71' @ 0.38 hrs Storage= 61,662 cf

Plug-Flow detention time= 28.3 min calculated for 88,612 cf (95% of inflow)

Center-of-Mass det. time= 27.6 min (41.1 - 13.5)

Volume	Invert Av	vail.Storage	Storage Description
#1	382.00'	64,856 cf	Custom Stage Data Listed below
Elevation (feet)	Cum.Stor (cubic-feet	=	
382.00		0	
383.00	1,68	6	
384.00	11,04	5	
385.00	25,74	6	
386.00	53,76	4	
387.00	64,85	6	

Device	Routing	Invert	Outlet Devices
#1	Primary	382.00'	24.0" Round RCP_Round 24"
	•		L= 20.0' RCP, square edge headwall, Ke= 0.500
			Inlet / Outlet Invert= 382.00' / 381.00' S= 0.0500 '/' Cc= 0.900
			n= 0.013 Concrete pipe, bends & connections, Flow Area= 3.14 sf
#2	Secondary	386.50'	15.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s)
#3	Device 1	384.00'	15.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s)
#4	Device 1	382 00'	6.0" Vert. Orifice/Grate C= 0.600. Limited to weir flow at low heads

Primary OutFlow Max=29.14 cfs @ 0.38 hrs HW=386.71' (Free Discharge)


-1=RCP_Round 24" (Inlet Controls 29.14 cfs @ 9.28 fps)

-3=Sharp-Crested Rectangular Weir (Passes < 211.06 cfs potential flow)


-4=Orifice/Grate (Passes < 2.00 cfs potential flow)

Secondary OutFlow Max=4.75 cfs @ 0.38 hrs HW=386.71' (Free Discharge) **2=Sharp-Crested Rectangular Weir** (Weir Controls 4.75 cfs @ 1.50 fps)

Pond 1P: Regional Detention Basin



Pond 1P: Regional Detention Basin



Summerwood Gym 3 AR - Little Rock 50-yr Du Prepared by Phillip Lewis Engineering HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Stage-Area-Storage for Pond 1P: Regional Detention Basin

		_	
Elevation	Storage	Elevation	Storage
(feet)	(cubic-feet)	(feet)	(cubic-feet)
382.00	0	384.60	19,866
382.05	84	384.65	20,601
382.10	169	384.70	21,336
382.15	253	384.75	22,071
382.20	337	384.80	22,806
382.25	422	384.85	23,541
382.30	506	384.90	24,276
382.35	590	384.95	25,011
382.40	674	385.00	25,746
382.45	759	385.05	27,147
382.50	843	385.10	28,548
382.55	927	385.15	29,949
382.60	1,012	385.20	31,350
382.65	1,096	385.25	32,751
382.70	1,180	385.30	34,151
382.75	1,265	385.35	35,552
382.80	1,349	385.40	36,953
382.85	1,433	385.45	38,354
382.90	1,517	385.50	39,755
382.95	1,602	385.55	41,156
383.00	1,686	385.60	42,557
383.05	2,154	385.65	43,958
383.10	2,622	385.70	45,359
383.15	3,090	385.75	46,760
383.20	3,558	385.80	48,160
383.25	4,026	385.85	49,561
383.30	4,494	385.90	50,962
383.35	4,962	385.95	52,363
383.40	5,430	386.00	53,764
383.45	5,898	386.05	54,319
383.50	6,366	386.10	54,873
383.55	6,833	386.15	55,428
383.60	7,301	386.20	55,982
383.65	7,769	386.25	56,537
383.70	8,237	386.30	57,092
383.75	8,705	386.35	57,646
383.80	9,173	386.40	58,201
383.85	9,641	386.45	58,755
383.90	10,109	386.50	59,310
383.95	10,577	386.55	59,865
384.00	11,045	386.60	60,419
384.05	11,780	386.65	60,974
384.10	12,515	386.70	61,528
384.15	13,250	386.75	62,083
384.20	13,985	386.80	62,638
384.25	14,720	386.85	63,192
384.30	15,455	386.90	63,747
384.35	16,190	386.95	64,301
384.40	16,925	387.00	64,856
384.45	17,660		
384.50	18,396		
384.55	19,131		
		l	

HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Link Post: Post Development


Inflow Area = 833,557 sf, 83.14% Impervious, Inflow Depth > 1.34" for 50-yr event

Inflow = 33.94 cfs @ 0.38 hrs, Volume= 93,123 cf

Primary = 33.94 cfs @ 0.38 hrs, Volume= 93,123 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs

Link Post: Post Development



HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC


Summary for Subcatchment DB-B1: Drainage Basin B1

Runoff = 19.38 cfs @ 0.09 hrs, Volume= 17,438 cf, Depth= 1.60" Routed to Pond 1P : Regional Detention Basin

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 100-yr Duration=15 min, Inten=6.52 in/hr

	Α	rea (sf)	С	Description	1	
_	1	30,996	0.98			
	130,996			100.00% Ir	npervious A	Area
	Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
	5.0					Direct Entry

Subcatchment DB-B1: Drainage Basin B1



HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC


Summary for Subcatchment DB-B2: Drainage Basin B2

Runoff = 15.30 cfs @ 0.09 hrs, Volume= 13,769 cf, Depth= 1.52" Routed to Pond 1P : Regional Detention Basin

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 100-yr Duration=15 min, Inten=6.52 in/hr

	Α	rea (sf)	С	Description	Description				
_		87,200	0.98						
_		21,800	0.74						
	1	109,000	0.93	Weighted Average					
		21,800		20.00% Pervious Area					
	87,200 80.00% Impervious Ar				pervious Aı	Area			
	Тс	Length	Slope	Velocity	Capacity	Description			
	(min)	(feet)	(ft/ft)	•	(cfs)	·			
-		(ieet)	(11/11)	(10/560)	(CIS)				
	5.0					Direct Entry.			

Subcatchment DB-B2: Drainage Basin B2



HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC


Summary for Subcatchment DB-B3: Drainage Basin B3

Runoff = 77.87 cfs @ 0.25 hrs, Volume= 70,080 cf, Depth= 1.52" Routed to Pond 1P : Regional Detention Basin

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 100-yr Duration=15 min, Inten=6.52 in/hr

_	Aı	rea (sf)	С	Description	1	
Ī	4	43,807	0.98			
	1	10,952	0.74			
	5	54,759	0.93	Weighted A	Average	
110,952 20.00% Pervious Area					ea	
	4	43,807		80.00% Im	pervious A	Area
	Тс	Length	Slope	Velocity	Capacity	Description
_	(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	
	15.0					Direct Entry.

Subcatchment DB-B3: Drainage Basin B3



HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Subcatchment DB-B4: Drainage Basin B4


Runoff = 5.45 cfs @ 0.09 hrs, Volume= 4,902 cf, Depth= 1.52"

Routed to Link Post: Post Development

Runoff by Rational method, Rise/Fall=1.0/1.0 xTc, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs AR - Little Rock 100-yr Duration=15 min, Inten=6.52 in/hr

	Area (sf)	С	Description	1			
	31,042	0.98					
	7,760	0.74					
	38,802	0.93	Weighted /	Average			
	7,760		20.00% Pervious Area				
	31,042		80.00% Impervious Area				
т.		Clana	\/a a=:6.	Cit.	Description		
To	U		,	Capacity	Description		
(min)) (feet)	(ft/ft)	(ft/sec)	(cfs)			
5.0)				Direct Entry, 15		

Subcatchment DB-B4: Drainage Basin B4



Printed 9/19/2023

HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Pond 1P: Regional Detention Basin

Inflow Area = 794,755 sf, 83.30% Impervious, Inflow Depth = 1.53" for 100-yr event

Inflow 112.75 cfs @ 0.25 hrs, Volume= 101.287 cf

46.71 cfs @ 0.35 hrs, Volume= 96,644 cf, Atten= 59%, Lag= 6.1 min Outflow

30.20 cfs @ Primary 0.35 hrs, Volume= 90,003 cf

Routed to Link Post: Post Development

0.35 hrs, Volume= Secondary = 16.51 cfs @ 6,641 cf

Routed to Link Post: Post Development

Routing by Stor-Ind method, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs

Peak Elev= 386.99' @ 0.35 hrs Storage= 64,697 cf

Plug-Flow detention time= 26.6 min calculated for 96,322 cf (95% of inflow)

Center-of-Mass det. time= 26.4 min (39.9 - 13.5)

Volume	Invert Av	ail.Storage	Storage Description
#1	382.00'	64,856 cf	Custom Stage Data Listed below
Elevation (feet)	Cum.Store (cubic-feet		
382.00	()	
383.00	1,686	6	
384.00	11,045	5	
385.00	25,746	6	
386.00	53,764	ļ	
387.00	64,856	6	

Device	Routing	Invert	Outlet Devices
#1	Primary	382.00'	24.0" Round RCP_Round 24"
	•		L= 20.0' RCP, square edge headwall, Ke= 0.500
			Inlet / Outlet Invert= 382.00' / 381.00' S= 0.0500 '/' Cc= 0.900
			n= 0.013 Concrete pipe, bends & connections, Flow Area= 3.14 sf
#2	Secondary	386.50'	15.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s)
#3	Device 1	384.00'	15.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s)
#4	Device 1	382.00'	6.0" Vert. Orifice/Grate C= 0.600 Limited to weir flow at low heads

Primary OutFlow Max=30.20 cfs @ 0.35 hrs HW=386.99' (Free Discharge)

_1=RCP_Round 24" (Inlet Controls 30.20 cfs @ 9.61 fps)


-3=Sharp-Crested Rectangular Weir (Passes < 242.94 cfs potential flow)

-4=Orifice/Grate (Passes < 2.06 cfs potential flow)


Secondary OutFlow Max=16.48 cfs @ 0.35 hrs HW=386.99' (Free Discharge) **2=Sharp-Crested Rectangular Weir** (Weir Controls 16.48 cfs @ 2.28 fps)

HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Pond 1P: Regional Detention Basin



Pond 1P: Regional Detention Basin



Stage-Area-Storage for Pond 1P: Regional Detention Basin

Classatiana	Ctanana	l =14:	Ctanana
Elevation	Storage (cubic-feet)	Elevation	Storage
(feet)		(feet)	(cubic-feet)
382.00	0	384.60	19,866
382.05	84	384.65	20,601
382.10	169	384.70	21,336
382.15	253	384.75	22,071
382.20	337	384.80	22,806
382.25	422	384.85	23,541
382.30	506	384.90	24,276
382.35	590	384.95	25,011
382.40	674	385.00	25,746
382.45	759	385.05	27,147
382.50	843	385.10	28,548
382.55	927	385.15	29,949
382.60	1,012	385.20	31,350
382.65	1,096	385.25	32,751
382.70	1,180	385.30	34,151
382.75	1,265	385.35	35,552
382.80	1,349	385.40	36,953
382.85	1,433	385.45	38,354
382.90	1,517	385.50	39,755
382.95	1,602	385.55	41,156
383.00	1,686	385.60	42,557
383.05	2,154	385.65	43,958
383.10	2,622	385.70	45,359
383.15	3,090	385.75	46,760
383.20	3,558	385.80	48,160
383.25	4,026	385.85	49,561
383.30	4,494	385.90	50,962
383.35	4,962	385.95	52,363
383.40	5,430	386.00	53,764
383.45	5,898	386.05	54,319 54,973
383.50	6,366	386.10	54,873
383.55	6,833 7,304	386.15	55,428 55,000
383.60	7,301	386.20	55,982
383.65 383.70	7,769	386.25 386.30	56,537
383.75	8,237		57,092 57,646
383.80	8,705 9,173	386.35 386.40	57,646 58,201
383.85	9,173	386.45	58,201 58,755
383.90	10,109	386.50	59,310
383.95	10,109	386.55	59,865
384.00	11,045		60,419
384.05	11,780	386.60 386.65	60,974
384.10	12,515	386.70	61,528
384.15	13,250	386.75	62,083
384.20	13,985	386.80	62,638
384.25	14,720	386.85	63,192
384.30	15,455	386.90	63,747
384.35	16,190	386.95	64,301
384.40	16,925	387.00	64,856
384.45	17,660	307.00	04,030
384.50	18,396		
384.55	19,131		
004.00	10, 101		
		1	

Summerwood Gym 3

AR - Little Rock 100-yr Duration=15 min, Inten=6.52 in/hr Printed 9/19/2023

Prepared by Phillip Lewis Engineering
HydroCAD® 10.20-2f s/n 12520 © 2022 HydroCAD Software Solutions LLC

Summary for Link Post: Post Development


Inflow Area = 833,557 sf, 83.14% Impervious, Inflow Depth > 1.46" for 100-yr event


Inflow = 46.71 cfs @ 0.35 hrs, Volume= 101,545 cf

Primary = 46.71 cfs @ 0.35 hrs, Volume= 101,545 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs

Link Post: Post Development






09/20/2023

OVERALL SITE PLAN

SHEET NUMBER:





SHEET ISSUE DATE: 09/20/2023


SITE PLAN


C1.2

















NOTE: HANDICAP SIGNAGE SHALL BE IN STRICT COMPLIANCE WITH CURRENT FEDERAL AND LOCAL LAW REQUIREMENTS

HANDICAP SIGN DETAIL







2'-0" CONCRETE CURB & GUTTER NOT TO SCALE



CONCRETE FLUME DETAIL

NOT TO SCALE

GYMNASIUM 7817 Hwy 5 N Bryant, Arkansas

PROJECT NUMBER:

ENGINEERING,


LEWIS


PHILLIP

REVISION:

SHEET ISSUE DATE: 09/20/2023

SITE DETAILS





EL = 384.00'

EL = 384.00'


24" DIAMETER RCP INVERT EL = 269.50'
6" DIAMETER PVC PIPE INVERT EL = 269.50

INSTALL 12" ORIFICE GRATE AT THIS LOCATION (SEE DETAIL BELOW)

OUT PAD W; 2"-3"
DIAMETER CLEAN STONE

DETENTION POND OUTLET STRUCTURE DETAIL

NOT TO SCALE



12" ORIFICE TRASH SCREEN

DETAILED ABOVE IS THE "TRASHRACK LPG-12" SCREEN. SIMILAR PRODUCT IS ALLOWED

SUMMERWOC

P LEWIS ENGINEERING, I ructural + Civil Consultants

PHILLIP

PRELIMINARY RUCTION

PROJECT NUMBER:

SHEET ISSUE DATE: 09/20/2023


PAGE TITLE:

DETENTION PLAN

SHEET NUMBER:

1" = 10'-0"






PRE DRAINAGE MAP

C1.8



POST DRAINAGE MAP C1.9




WIS ENGINEERING, INC.

aral + Civil Consultants

erstate 30 | Bryant, Arkansas
PH: 501-350-9840

PHILLIP LE
Struct
33620 Int



EVISION:

ERWOOD SPOR'

GYMNAS 7817 HV

PRELIMINARY RUCTION

PROJECT NUMBER

SHEET ISSUE DATE:

09/20/2023

SANITARY SEWER PLAN



NOTES AND SPECIFICATIONS:

FENCE.

1. POSTS SHALL BE A MINIMUM OF 36 INCHES CONSTRUCTED OF EITHER OF THE FOLLOWING MATERIALS: STEEL "T" OR "U" TYPE, OR 2" x 2" HARDWOOD.

2. WOVEN WIRE USED AS ADDITIONAL FENCE SUPPORT SHALL BE MINIMUM 14.5 GA. WITH 6" MAXIMUM SPACING.

3. WOVEN WIRE SHALL BE PLACED ALONG THE UPHILL SIDE OF THE FENCE AND FASTENED WITH WIRE TIES OR 1" STAPLES ALONG THE UPHILL SIDE OF THE

4. FILTER FABRIC SHALL BE FASTENED TO WOVEN WIRE ACCORDING TO MANUFACTURE'S RECOMMENDATION, OR WITH TIES EVERY 24" AT THE TOP

AND MID-SECTIONS. 5. WHERE TWO PIECES OF FILTER FABRIC ADJOIN EACH OTHER THEY SHALL BE

OVERLAPPED BY 6 INCHES AND FOLDED TOGETHER. 6. WHERE TWO POSTS MEET TO JOIN FENCE SECTIONS, THE TOPS OF THE


POSTS SHALL BE SECURED TOGETHER WITH WIRE. 7. THE FENCE SHALL BE CONSTRUCTED ALONG THE CONTOUR AS MUCH AS


8. ENDS OF FENCES SHALL BE EXTENDED UP THE SLOPE TO PRVENT RUNOFF FROM MIGRATING AROUND THE END OF THE FENCE.

9. INSPECTION OF THE FENCE SHALL BE PERFORMED WEEKLY, OR IMMEDIATELY AFTER A RAIN EVENT, OR WHEN BULGES APPEAR IN THE FENCE. ACCUMALTED SILT SHALL NOT BE ALLOWED TO EXCEED HALF THE HEIGHT OF THE FABRICA SEPARATION. COMPLETED PROMPTLY.

10. ACCUMULATED SILT SHALL BE REMOVED AND DISPOSED OF IN AN APPROVED SITE IN SUCH A MANNER THAT IT WILL NOT CONTRIBUTE TO OFF-SITE

11. ALL FENCING SHALL BE REMOVED WITH THE CONSTRUCTION SITE IS FULLY STABLIZED SO AS TO NOT IMPEDE STORM FLOW OR DRAINAGE. 12. PRE-FRABRICATED UNITS DO NOT REQUIRE THE USE OF WOVEN WIRE





─ 20" DIA CURLEX ® SEDIMENT LOG. OR APPROVED EQUAL


NOT TO SCALE

 REPAIR ALL RILLS OR GULLIES PRIOR TO INSTALLATION
2. INSTALL CHECK DAMS IN SWALES PERPENDICULAR

TO THE FLOWLINE 3. STAKE SEDIMENT LOGS IN PLACE WITH $1_8^{\rm H}$ " X $1_8^{\rm H}$ " WOODEN STAKES. DRIVE STAKES AT EACH END OF THE SEDIMENT LOG AT 2' (MAX) SPACING.

4. DRIVE STAKES INTO UNDISTURBED SOIL OF SWALE BOTTOM 16" (MIN). EXPOSE STAKES 2" MIN ABOVE TOP OF LOG.

5. PROVIDE SUFFICIENT LENGTH TO PREVENT WATER FROM FLOWING AROUND THE ENDS OF THE 6. DO NOT USE WITH SWALE GRADE > 5%



NOTES AND SPECIFICATIONS:

1. SEDIMENT LOGS SHOULD BE PLACED 180 FT APART BASED ON THE SLOPE OF THE SURFACE 2. THERE SHOULD BE THREE SEDIMENT LOGS USED IN THE DRAINAGE DITCH RUNNING SOUTH ALONG SKYLINE DR UNTIL IT MEETS THE LARGE DRAINAGE DITCH THAT RUNS ALONG THE FRONT OF THE DEALERSHIP

3. SHOULD BE INSTALLED FROM BOC TO THE EDGE OF THE ROW

CHECK DAM SPACING G (%) S (FT) 1 150 2 75 50 40 4 30

- CURLEX ® SEDIMENT LOG, OR APPROVED

SEDIMENT LOG

CONCRETE WASHOUT

NOT TO SCALE

NOTES (GENERAL): 1. SEE EROSION CONTROL DETAILS IN SWPPP FOR EROSION CONTROL 2. SEE SWPPP FOR INSTALLATION, MAINTENANCE, INSPECTION, AND RECORD

KEEPING REQUIREMENTS. 3. CONTRACTOR SHALL SHOW EROSION CONTROL MEASURES ON SITE MAP. 4. EROSION AND SEDIMENT CONTROL STRUCTURES TO MEET SWPPP DETAILS - APPENDIX D. 5. INSTALL ROCK DITCH CHECKS OR SAND BAG SHECKS AS NECESSARY TO PREVENT SCOUR UNTIL LANDSCAPING IS ESTABLISHED.


6. CONTRACTOR MUST PLACE SEDIMENT BASIN WITH SEDIMENT FENCE OUTLET FOR ANY SEDIMENT CONTAMINATED DEWATERING DISCHARGE. 7. CONTRACTOR TO CONSTRUCT CONCRETE WAS OUT SUMP, AS NEEDED AND SHOWN ON CONSTRUCTION PLANS. DO NOT DISCHARGE TO SURFACE. 8. FINAL SLOPE WILL BE SAME DIRECTION AS EXISTING SLOPE.





DISTURBED AREA

BUFFER ZONE

SEDIMENT FENCE WITH WIRE BACKING DRAINAGE DIRECTION








ENGINEERING,

PHILLIP



GYMNASIUM 7817 Hwy 5 N Bryant, Arkansas

PROJECT NUMBER:

SHEET ISSUE DATE: 09/20/2023

SWPPP PH. 1



NOTES AND SPECIFICATIONS: 1. POSTS SHALL BE A MINIMUM OF 36 INCHES CONSTRUCTED OF EITHER OF THE FOLLOWING MATERIALS: STEEL "T" OR "U" TYPE, OR 2" x 2" HARDWOOD. 2. WOVEN WIRE USED AS ADDITIONAL FENCE SUPPORT SHALL BE MINIMUM 14.5 GA. WITH 6" MAXIMUM SPACING. 3. WOVEN WIRE SHALL BE PLACED ALONG THE UPHILL SIDE OF THE FENCE AND FASTENED WITH WIRE TIES OR 1" STAPLES ALONG THE UPHILL SIDE OF THE

4. FILTER FABRIC SHALL BE FASTENED TO WOVEN WIRE ACCORDING TO MANUFACTURE'S RECOMMENDATION, OR WITH TIES EVERY 24" AT THE TOP AND MID-SECTIONS.

5. WHERE TWO PIECES OF FILTER FABRIC ADJOIN EACH OTHER THEY SHALL BE OVERLAPPED BY 6 INCHES AND FOLDED TOGETHER. 6. WHERE TWO POSTS MEET TO JOIN FENCE SECTIONS, THE TOPS OF THE

POSTS SHALL BE SECURED TOGETHER WITH WIRE. 7. THE FENCE SHALL BE CONSTRUCTED ALONG THE CONTOUR AS MUCH AS


8. ENDS OF FENCES SHALL BE EXTENDED UP THE SLOPE TO PRVENT RUNOFF FROM MIGRATING AROUND THE END OF THE FENCE.


POSSIBLE.

9. INSPECTION OF THE FENCE SHALL BE PERFORMED WEEKLY, OR IMMEDIATELY AFTER A RAIN EVENT, OR WHEN BULGES APPEAR IN THE FENCE. ACCUMALTED SILT SHALL NOT BE ALLOWED TO EXCEED HALF THE HEIGHT OF THE FABRICA SEPARATION. COMPLETED PROMPTLY.

10. ACCUMULATED SILT SHALL BE REMOVED AND DISPOSED OF IN AN APPROVED SITE IN SUCH A MANNER THAT IT WILL NOT CONTRIBUTE TO OFF-SITE

11. ALL FENCING SHALL BE REMOVED WITH THE CONSTRUCTION SITE IS FULLY STABLIZED SO AS TO NOT IMPEDE STORM FLOW OR DRAINAGE. 12. PRE-FRABRICATED UNITS DO NOT REQUIRE THE USE OF WOVEN WIRE FENCE.





- 20" DIA CURLEX ® SEDIMENT LOG. OR APPROVED EQUAL

 REPAIR ALL RILLS OR GULLIES PRIOR TO INSTALLATION
2. INSTALL CHECK DAMS IN SWALES PERPENDICULAR

TO THE FLOWLINE 3. STAKE SEDIMENT LOGS IN PLACE WITH 11/8" X 11/8" WOODEN STAKES. DRIVE STAKES AT EACH END OF THE SEDIMENT LOG AT 2' (MAX) SPACING. 4. DRIVE STAKES INTO UNDISTURBED SOIL OF SWALE BOTTOM 16" (MIN). EXPOSE STAKES 2" MIN ABOVE

TOP OF LOG. 5. PROVIDE SUFFICIENT LENGTH TO PREVENT WATER FROM FLOWING AROUND THE ENDS OF THE 6. DO NOT USE WITH SWALE GRADE > 5%

TRENCH 2" MIN -TYPICAL CROSS SECTION N.T.S. - CURVE ENDS UPSTREAM TO PREVENT FLOW AROUND THE ENDS. SEE NOTE 5.

NOTES AND SPECIFICATIONS:

3. SHOULD BE INSTALLED FROM BOC TO THE EDGE OF THE ROW

1. SEDIMENT LOGS SHOULD BE PLACED 180 FT APART BASED ON THE SLOPE OF THE SURFACE 2. THERE SHOULD BE THREE SEDIMENT LOGS USED IN THE DRAINAGE DITCH RUNNING SOUTH ALONG SKYLINE DR UNTIL IT MEETS THE LARGE DRAINAGE DITCH THAT RUNS ALONG THE FRONT OF THE DEALERSHIP

CHECK DAM SPACING G (%) S (FT) 1 150 2 75 50 40 4 30

SEDIMENT LOG

20" DIA CURLEX ® —

OR APPROVED

SEDIMENT LOG,

NOT TO SCALE

- CURLEX ® SEDIMENT LOG, OR APPROVED

NOTES (GENERAL):

1. SEE EROSION CONTROL DETAILS IN SWPPP FOR EROSION CONTROL 2. SEE SWPPP FOR INSTALLATION, MAINTENANCE, INSPECTION, AND RECORD KEEPING REQUIREMENTS.

3. CONTRACTOR SHALL SHOW EROSION CONTROL MEASURES ON SITE MAP. 4. EROSION AND SEDIMENT CONTROL STRUCTURES TO MEET SWPPP DETAILS - APPENDIX D. 5. INSTALL ROCK DITCH CHECKS OR SAND BAG SHECKS AS NECESSARY TO PREVENT SCOUR UNTIL LANDSCAPING IS ESTABLISHED. 6. CONTRACTOR MUST PLACE SEDIMENT BASIN WITH SEDIMENT FENCE OUTLET FOR ANY SEDIMENT CONTAMINATED DEWATERING DISCHARGE. 7. CONTRACTOR TO CONSTRUCT CONCRETE WAS OUT SUMP, AS NEEDED


AND SHOWN ON CONSTRUCTION PLANS. DO NOT DISCHARGE TO SURFACE.


8. FINAL SLOPE WILL BE SAME DIRECTION AS EXISTING SLOPE.


LEGEND

DISTURBED AREA

BUFFER ZONE SEDIMENT FENCE WITH WIRE BACKING DRAINAGE DIRECTION







ENGINEERING,

PHILLIP

REVISION:

GYMNASIUM 7817 Hwy 5 N Bryant, Arkansas

PROJECT NUMBER:

SHEET ISSUE DATE: 09/20/2023

SWPPP PH. 2



BRAND BOOK

Dak's Market

Address: 2725 Springhill Rd Bryant, AR 72022

June 7th, 2023



1312 E. 1st Clovis, NM 88101 1-575-763-5623 Fax: 1-575-763-6365



Created by: Glen Southard Date: 6-8-23


Last Edited by: Glen Southard

Date: 6-19-23





Site Plan




Proposed

Defek

Existing





ID Sign

12" Extrusion - White .177 - White 1st Surface Red Vinyl Letters 95 in H x 90.75 in W 89 in H x 85 in W 96 in H x 91.75 in W 2" - White 92 in H x 87.75 in W Visual Opening: Face Material: Upper Pan: Pan Depth: Face Size: Retainer: Cabinet: Cabinet: Type:


Price Sign

1st Surface Red/Green Letters 23 in H x 90.75 in W 12" Extrusion - White 2" - White .177 - White 20 in H x 87.75 in W 24 in H x 91.75 in W Visual Opening: Face Material: Face Size: Retainer: Cabinet: Cabinet: Type:

- Poles to be painted White
 Remove Crossbrace at top of Poles
 New MID Cabinet and Faces.
 Reface and Reuse Existing LED Digits in Price Sign

Canopy 1

.18 in.









City of Bryant, Arkansas Community Development 210 SW 3rd Street Bryant, AR 72022 501-943-0943

SIGN PERMIT APPLICATION

Applicants are advised to read the Sign Ordinance prior to completing and signing this form. The Sign Ordinance is available at www.cityofbryant.com under the Planning and Community Development tab.

Developm	ent tab.
Date: 9/8/23	Note: Electrical Permits may be Required, Please contact the Community Development Office for more information.
Sign Co. or Sign Owner	Property Owner
Name EDWARDS SIBN CO.	Name_DELECTION
Address 2208 AIRPORT RD.	Address 2725 SPRINGHILL RD
City, State, Zip HOT SPRINGS, NR 71913	
Phone 501 767 6525	Phone SAME
Alternate Phone 501 627 6226	Alternate Phone
GENERAL INFORMATION	1
Name of Business SPRINGHILL GR	DCERY / HH COUNTRY STURD
Address/Location of sign 27 25 SPRIA	BHULRD
Zoning Classification	
Please use following page to provide details on the sprovided on this application, a Site Plan showing place	signs requesting approval. Along with information

Please use following page to provide details on the signs requesting approval. Along with information provided on this application, a Site Plan showing placement of sign(s) and any existing sign(s) on the property is required to be submitted. Renderings of the sign(s) showing the correct dimensions is also required to be submitted with the application. A thirty-five dollar (\$35) per sign payment will be collected at the time of permit issuance. According to the Sign Ordinance a fee for and sign variance or special sign permit request shall be one hundred dollars (\$100). Additional documentation may be required by Sign Administrator.

READ CAREFULLY BEFORE SIGNING

, do hereby certify that all information contained within this application is true and correct. I fully understand that the terms of the Sign Ordinance supersede the Sign Administrator's approval and that all signs must fully comply with all terms of the Sign Ordinance regardless of approval. I further certify that the proposed sign is authorized by the owner of the property and that I am authorized by the property owner to make this application. I understand

EXISTING SIGN







UNLEADED

DIESEL





PROPOSED SIGN

that no sign may be placed in public right of way. I understand that I must comply with all Building and Electrical Codes and that it is my responsibility to obtain all necessary permits.

Use table below to enter information regarding each sign for approval. Please use each letter to reference each sign rendering.

SIGN		Dimensions (Height, Length, Width)	Sqft (Measured in whole as rectangle)	Height of Sign (Measured from lot surface)		Column for Admin Certifying Approval
	EXISTIN	4		Top of Sign	Bottom of Sign	тергочи
Α	POLE SIGN	96"×92"x12	56	211	13 PT	
В	EXISTING	96×42"	28	13	9FT-61	V
С	1 RUCE 5161	y v z z z				
E						
F -	-,					1
G			in the same			4

(A.) REMOVE EXISTING	108"X80" CURVEDAOP SIGN
REPLACE WITH	96" ×92" SQUARE LIGHTED SIGN
(B) CHANGE FACES IN	EXISTING 92"X42" PRICE SIGN